DATASHEET

19" Wall Housing 15U, Fixed, 1-Part, RAL9005, Depth 450 mm









General data

The 19-inch 15U, 450 mm deep 15U fixed, one-piece wall enclosure in black RAL 9005 is designed for use in controlled indoor areas. The pre-assembled sheet steel construction with welded frame makes it easy to transport and assemble and provides a stable base for the installation of 19-inch components.

• 15U in 19-inch design with 450 mm depth – Creates a compact installation situation for 19-inch components and supports a well-defined assembly.
• Pre-assembled sheet steel construction with welded frame – Reduces assembly effort and provides a stable base during operation.
• Glass door with viewing window made of certified safety glass and replaceable door hinge – Enables visual inspection of the equipment and adapts flexibly to the installation situation.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and self-ventilated design. The IP20 protection class, the load capacity of 50 kg and the powder-coated surface in black are designed for use in controlled indoor areas. Cable entries over the roof, floor and twice over the back, each measuring 250 x 70 mm, support clean integration of the components. The maximum distance between the 19-inch levels of 365 mm creates additional scope for assembly.

Technical details

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing 15U, Fixed, 1-Part, RAL9005, Depth 450 mm

- Number of doors: 1
- Degree of protection: IP20
- Type of ventilation: passive
- Mounting level: front
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Front door locking: Latch lock
- Front door opening angle: > 120°
- Replaceable profile half-cylinder in front door: optional (compact swing handle item no. 699989)
- Cable entry roof/floor: roof + floor + 2 x back, each 250 x 70 mm
- Max. distance of the 19" planes: 365 mm
- Payload: 50 kg
- Finish of the surface: powder-coated
- Colour: black
- Scope of delivery: 1x cabinet, 1x brush strip, 1x cage nut set (pack of 20 pcs.), 2x wrench
- Packaging: Supplied in transport packaging, from 30 kg / 12 U on a one-way pallet

Technical properties	
Cabinet Series	19" Wall Housing 1-Part, pre-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 250 x 70 mm
Degree of protection	IP20
Demountable	False
Door hinge reversible front door	Yes
Door opening angle front door	120 °
Frame	welded
Installation depth min. - max.	400 mm
Material	Steel
Max. spacing of the 19" levels	365 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	Delivery in transport packaging, from 30 kg / 12 U on a disposable pallet

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing 15U, Fixed, 1-Part, RAL9005, Depth 450 mm

Scope of delivery	1x Cabinet, 1x brush strip, 1x cage nut set (Pack size 20 pieces), 2x keys
Structure/Use	Steel sheet housing with welded frame, pre-assembled, self-ventilated.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691706VTS.45	19" Wall Housing 6U, Fixed, 1-Part, RAL9005, Depth 450 mm	black	450 mm	330 mm	50 kg	6 U	600 mm	9005
691709VTS.45	19" Wall Housing 9U, Fixed, 1-Part, RAL9005, Depth 450 mm	black	450 mm	465 mm	50 kg	9 U	600 mm	9005
691712VTS.45	19" Wall Housing 12U, Fixed, 1-Part, RAL9005, Depth 450 mm	black	450 mm	600 mm	50 kg	12 U	600 mm	9005
691715VTS.45	19" Wall Housing 15U, Fixed, 1-Part, RAL9005, Depth 450 mm	black	450 mm	730 mm	50 kg	15 U	600 mm	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION