DATASHEET

19" Wall Housing IP55, 20U, Steel Door, Depth 600 mm, RAL7035

General data

The 19" IP55 wall enclosure with a depth of 600 mm and RAL 7035 is designed as a robust solution for demanding installation environments. The fully pre-assembled sheet steel enclosure with welded body provides a stable base for the 19-inch installation and includes 20 U.

• 20 U in 19-inch increments with a depth of 600 mm – Creates a clearly defined installation situation and provides reserves for structured assembly.
• Fully pre-assembled sheet steel housing with welded body – Reduces assembly effort and provides a stable base during operation.
• IP55 rating with PUR seals on roof and door – Increases protection against dust and water in demanding applications.

In terms of technical design, the housing combines a mounting level at the front and rear with passive ventilation. The IP55 protection class, the load capacity of 100 kg and the powder-coated surface are designed for environments with increased requirements for dust and water protection. The cable entry in the floor with PG glands and PVC cable grommets as well as the maximum distance of the 19" levels of 490 mm support a clean integration of the components.

Technical details
• Number of doors: 1

This datasheet was created automatically on 09-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing IP55, 20U, Steel Door, Depth 600 mm, RAL7035

- Degree of protection: IP55
- Type of ventilation: passive
- Air inlet bottom: bottom, PG glands 1 x PG48, 2 x PG21, 3 x Ø 20 mm PVC cable grommets
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, not openable
- Mounting level: front and rear
- Front door design: one-piece steel door
- Front door opening angle: approx. 120 °
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 4x wall bracket, 2x keys
- Packaging: 1 carton
- Width: 600 mm
- Height: 1000 mm
- Depth: 600 mm
- Load capacity: 100 kg
- Installation depth min. - max.: 530 mm
- Max. distance of the 19" levels: 490 mm

Technical properties	
Cabinet Series	19" Wall Housing IP55
Cable entry roof/floor	Floor, PG glands 1 x PG48, 2 x PG21, 3 x Ø 20 mm PVC grommet
Degree of protection	IP55
Demountable	False
Door hinge reversible front door	No
Door opening angle front door	ca. 120 °
Frame	welded
Installation depth min. - max.	530 mm
Material	Steel
Max. spacing of the 19" levels	490 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
Number of doors	1
PHC replaceable front door	Yes, DIN18252 (30/10 mm)
Packaging	1 carton
Scope of delivery	1x Cabinet, 4x wall mount, 2x keys

This datasheet was created automatically on 09-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing IP55, 20U, Steel Door, Depth 600 mm, RAL7035

Structure/Use	Steel sheet housing with welded body, fully pre-assembled. PUR seals on roof and door for dust and water protection.
Surface finishing	Powder coating
Type of front door	Steel door 1-part
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691707IP55.2	19" Wall Housing IP55, 7U, Steel Door, Depth 600 mm, RAL7035	grau	600 mm	410 mm	100 kg	7 U	600 mm	7035
691709IP55.2	19" Wall Housing IP55, 9U, Steel Door, Depth 600 mm, RAL7035	grau	600 mm	500 mm	100 kg	9 U	600 mm	7035
691712IP55.2	19" Wall Housing IP55, 12U, Steel Door, Depth 600 mm, RAL7035	grau	600 mm	630 mm	100 kg	12 U	600 mm	7035
691716IP55.2	19" Wall Housing IP55, 16U, Steel Door, Depth 600 mm, RAL7035	grau	600 mm	810 mm	100 kg	16 U	600 mm	7035
691720IP55.2	19" Wall Housing IP55, 20U, Steel Door, Depth 600 mm, RAL7035	grau	600 mm	1000 mm	100 kg	20 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION