


DATASHEET

19" Wall Housing Flat Pack 21U, Depth 600 mm, RAL7035



General data

The 19" Flat Pack wall-mounted enclosure in RAL 7035 with a depth of 600 mm is designed for the safe storage of 19-inch components. The unassembled flat-pack design reduces transport volume and makes storage easier. The screwed sheet steel enclosure with fixed frame creates a stable basis for self-assembly and later removal.

- 21U in 19-inch increments with a depth of 600 mm – Provides a well-defined installation space for network and IT components.
- Flat-pack design, delivered unassembled – Reduces transport and storage costs and simplifies on-site assembly.
- Front door as a glass door with viewing window made of certified safety glass and replaceable door hinge – Enables visual inspection and supports flexible installation situations.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and self-ventilated design. The IP20 protection class, the powder-coated surface and the load capacity of 60 kg are designed for use in controlled indoor areas. Cable entries over the roof, floor and rear support clean cable routing. The maximum distance of the 19" levels of 490 mm complements the integration of larger components.

Technical details

- Number of doors: 1
- Degree of protection: IP20
- Type of ventilation: passive
- With earthing: Yes

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing Flat Pack 21U, Depth 600 mm, RAL7035

- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Mounting level: front
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Front door locking: Latch lock
- Reversible front door hinging: Yes
- Replaceable profile half-cylinder in front door: optional (compact swing handle item no. 699989)
- Scope of delivery: 1x cabinet, earthing cable, 2x keys
- Packaging: 1 carton

Technical properties	
Cabinet Series	19" Wall Housing FLAT PACK, un-assembled
Cable entry roof/floor	Roof + base + 2 x back, each 230 x 41 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Frame	screwed together, unassembled
Installation depth min. - max.	530 mm
Material	Steel
Max. spacing of the 19" levels	490 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	optional (compact swivel lever item no. 699989)
Packaging	1 carton
Scope of delivery	1x Cabinet, grounding cable, 2x keys
Structure/Use	Steel sheet housing with very solid frame, self-ventilated, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing Flat Pack 21U, Depth 600 mm, RAL7035

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691709FGR.2	19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL7035	grey	600 mm	500 mm	60 kg	9 U	570 mm	7035
691712FGR.2	19" Wall Housing Flat Pack 12U, Depth 600 mm, RAL7035	grey	600 mm	635 mm	60 kg	12 U	570 mm	7035
691715FGR.2	19" Wall Housing Flat Pack 15U, Depth 600 mm, RAL7035	grey	600 mm	770 mm	60 kg	15 U	570 mm	7035
691721FGR.2	19" Wall Housing Flat Pack 21U, Depth 600 mm, RAL7035	grey	600 mm	1040 mm	60 kg	21 U	570 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

