

DATASHEET

19" Wall Housing 12U, Depth 800 mm, Pre-Assembled, RAL9005



General data

The 19" wall enclosure with fixed frame, 12 U and 800 mm depth in black is designed as a robust solution for structured network and IT installations. The pre-assembled, dismantlable sheet steel construction creates a stable base and at the same time facilitates transport, storage and assembly.

- 12U in 19-inch version with 800 mm depth – Creates generous installation space for network and IT components and supports clear installation.
- Pre-assembled sheet steel housing with bolted frame – Reduces assembly effort and facilitates handling on site.
- Glass door with viewing window made of certified safety glass and replaceable door hinge – Enables visual inspection and adapts flexibly to the installation situation.

In terms of technical design, the housing combines a mounting level at the front and rear with passive ventilation and self-ventilated design. The IP20 protection class, the load capacity of 80 kg and the powder-coated surface are designed for use in controlled indoor areas. Cable entries over the roof, floor and rear as well as the steel construction support a clean and stable integration of the components.

Technical details

- Number of doors: 1
- Degree of protection: IP20

This datasheet was created automatically on 25-10-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing 12U, Depth 800 mm, Pre-Assembled, RAL9005

- Type of ventilation: passive
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Mounting level: front and rear
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Front door locking: Latch lock
- Reversible front door hinging: Yes
- Scope of delivery: 1x cabinet, 1x brush strip, 1x plastic cover for cable entry, 1x cage nut set (pack of 20 pcs.), 2x wrench
- Packaging: Delivered in transport packaging on a one-way pallet
- Cable entry roof/floor: roof + floor + back, each 145 x 70 mm
- Max. load capacity: 80 kg
- Colour: black
- Material: Steel

Technical properties	
Cabinet Series	19" Wall Housing Depth 800 mm, pre-assembled
Cable entry roof/floor	Roof + base + back, each 145 x 70 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Frame	screwed together, pre-assembled, disassemblable
Material	Steel
Model	With permanent frame
Modular spacing	482.6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
Number of doors	1
PHC replaceable front door	No
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover for cable entry, 1x cage nut set (Pack size 20 pieces), 2x keys
Structure/Use	Steel sheet housing with bolted frame, pre-assembled, self-ventilated, disassemblable.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	Crank

This datasheet was created automatically on 25-10-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing 12U, Depth 800 mm, Pre-Assembled, RAL9005

Type of ventilation	Passive
With earthing	True
With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Max. load capacity	Number of height units	Width	RAL-number
691912TS.80	19" Wall Housing 12U, Depth 800 mm, Pre-Assembled, RAL9005	Black	800 mm	634 mm	80 kg	80 kg	12 U	600 mm	7035
691916TS.80	19" Wall Housing 16U, Depth 800 mm, Pre-Assembled, RAL9005	Black	800 mm	812 mm	80 kg	80 kg	16 U	600 mm	7035
691920TS.80	19" Wall Housing 20U, Depth 800 mm, Pre-Assembled, RAL9005	Black	800 mm	990 mm	80 kg	80 kg	20 U	600 mm	7035
691922TS.80	19" Wall Housing 22U, Depth 800 mm, Pre-Assembled, RAL9005	Black	800 mm	1078 mm	80 kg	80 kg	22 U	600 mm	7035
691926TS.80	19" Wall Housing 26U, Depth 800 mm, Pre-Assembled, RAL9005	Black	800 mm	1256 mm	80 kg	80 kg	26 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-10-2026 . Technical changes reserved.

