

DATASHEET

Fronttür für Wandgehäuse 691912TS.80, mit Scharnieren und Schloss



General data

The one-piece front door for wall enclosures in black RAL 9005 is designed for the 600 mm cabinet width and complements the 12 U variants with a compact viewing solution with swing handle. The design is designed for clean integration into the enclosure system and for a clear front design.

- One-piece glass door with swing handle – Provides visibility of the equipment and combines ease of use with controlled access.
- Hinged door for 600 mm cabinet installation – Fits the defined wall enclosure format and supports a uniform front view.
- Transparent door design with 1-point locking mechanism – Enables quick control of the components and keeps the door reliably closed.

In terms of technical construction, the door combines a 515 mm wide and 545.3 mm high glass construction with side elements made of aluminium. The surface of the aluminium elements is powder-coated, the degree of protection is IP20 and the door opening angle is approx. 120°. Together with the 1-point quarter-turn latch and the 2 keys supplied, a functional solution for controlled access in the wall housing area is created.

Technical details

- Number of doors: 1
- Degree of protection: IP20
- Design: Hinged door
- Construction/use: Glass door, one-piece, with swing handle
- Transparent door version: Yes
- Type of closure: 1-point quarter-turn latch
- Surface finish: Powder-coated aluminium elements
- Colour: black
- RAL number: 9005

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

Fronttür für Wandgehäuse 691912TS.80, mit Scharnieren und Schloss

- For cabinet width: 600 mm
- Width for cabinet installation: 600 mm
- Width: 515 mm
- Height: 545.3 mm
- Depth: 22 mm
- Material: glass, side elements aluminium
- Door opening angle: approx. 120°
- Scope of delivery: door, incl. hinges, 2 x keys

Technical properties

Cabinet Series	Wall Housings 1/2-part
Degree of protection	IP20
Door opening angle	ca. 120 °
For Cabinet Width	600 mm
Material	Glass, side elements aluminium
Model	Stop door
Number of height units (U)	12
Profile half-cylinder exchangeable	False
Scope of delivery	Tür, inkl. Scharnieren, 2 x Schlüssel
Structure/Use	Glastür, einteilig, mit Schwenkhebel
Surface finishing	Aluminium elements powder-coated
Type of closure	Single-point latch locking
Version as glazed door	True

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	Depth	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
691912TS.TUR	Fronttür für Wandgehäuse 691912TS.80, mit Scharnieren und Schloss	600 mm	black	545.3 mm	515 mm	22 mm	9005	False	False
691916TS.TUR	Fronttür für Wandgehäuse 691916TS.80, mit Scharnieren und Schloss	600 mm	black	723.1 mm	515 mm	22 mm	9005	False	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Fronttür für Wandgehäuse 691912TS.80, mit Scharnieren und Schloss

691920TS.TUR	Fronttür für Wandgehäuse 691920TS.80, mit Scharnieren und Schloss	600 mm	black	900.9 mm	515 mm	22 mm	9005	False	False
691922TS.TUR	Fronttür für Wandgehäuse 691922TS.80, mit Scharnieren und Schloss	600 mm	black	989.9 mm	515 mm	22 mm	9005	False	False
691926TS.TUR	Fronttür für Wandgehäuse 691926TS.80, mit Scharnieren und Schloss	600 mm	black	1167.6 mm	515 mm	22 mm	9005	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

