

DATASHEET

Fronttür für Wandgehäuse 691916GR.80, mit Scharnieren und Schloss



General data

The front door element for wall enclosures in grey RAL 7035 is designed as a one-piece glass door for cabinet widths of 600 mm. The hinged door combines a compact design with visual inspection and a mechanically clearly defined design for 16 U.

- One-piece glass door with swing handle – Allows you to see the installation and supports easy operation at the front.
- 1-point forward locking with 2 keys – Secures access with a slim locking system and practical handling.
- Grey version according to RAL 7035 – Visually matches standardized housing series and facilitates integration into existing environments.

Structurally, the door is based on a glass version with aluminium side elements and is designed as a hinged door. With a width of 515 mm, a height of 723.1 mm and a depth of 22 mm, it is intended for precise front mounting in 600 mm cabinet widths. The transparent door design supports the visual inspection of the built-in components without having to open the cabinet.

Technical details

- Number of doors: 1
- Degree of protection: IP20
- With front door: Yes
- Mounting level: front
- Front door version: glass door, one-piece, with swing handle
- Front door opening angle: approx. 120 °
- Front door locking: 1-point pre-latch access
- Scope of delivery: door, incl. hinges, 2 x keys
- Number of rack units (U): 16 U
- Width for cabinet installation: 600 mm
- For cabinet width: 600 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

Fronttür für Wandgehäuse 691916GR.80, mit Scharnieren und Schloss

- Width: 515 mm
- Height: 723.1 mm
- Depth: 22 mm
- Colour: grey
- RAL number: 7035
- Transparent door version: Yes
- Material: glass, side elements aluminium
- Design: Hinged door

Technical properties

Cabinet Series	Wall Housings 1/2-part
Degree of protection	IP20
Door opening angle	ca. 120 °
For Cabinet Width	600 mm
Material	Glass, side elements aluminium
Model	Stop door
Number of height units (U)	12
Profile half-cylinder exchangeable	False
Scope of delivery	Tür, inkl. Scharnieren, 2 x Schlüssel
Structure/Use	Glastür, einteilig, mit Schwenkhebel
Surface finishing	Aluminium elements powder-coated
Type of closure	Single-point latch locking
Version as glazed door	True

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	Depth	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
691912GR.TUR	Fronttür für Wandgehäuse 691912GR.80, mit Scharnieren und Schloss	600 mm	grey	545.3 mm	515 mm	22 mm	7035	False	False
691916GR.TUR	Fronttür für Wandgehäuse 691916GR.80, mit Scharnieren und Schloss	600 mm	grey	723.1 mm	515 mm	22 mm	7035	False	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Fronttür für Wandgehäuse 691916GR.80, mit Scharnieren und Schloss

691920GR.TUR	Fronttür für Wandgehäuse 691920GR.80, mit Scharnieren und Schloss	600 mm	grey	900.9 mm	515 mm	22 mm	7035	False	False
691922GR.TUR	Fronttür für Wandgehäuse 691922GR.80, mit Scharnieren und Schloss	600 mm	grey	989.9 mm	515 mm	22 mm	7035	False	False
691926GR.TUR	Fronttür für Wandgehäuse 691926GR.80, mit Scharnieren und Schloss	600 mm	grey	1167.6 mm	515 mm	22 mm	7035	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

