

DATASHEET

Fronttür für Wandgehäuse 691920TS.80, mit Scharnieren und Schloss



General data

The fixed front door for wall enclosures in black RAL 9005 is designed for a cabinet width of 600 mm. The one-piece glass door design combines visual inspection with a robust, functional design for use on matching enclosures.

- One-piece glass door design with visual function – Allows visual inspection of the interior without opening the housing.
- 1-point latch locking with swing handle – Supports easy locking and practical operation in daily use.
- Version in black RAL 9005 for 600 mm cabinet widths – Ensures harmonious integration into corresponding wall enclosures.

The construction combines glass with aluminium side elements and a powder-coated surface. The IP20 protection class and the door opening angle of approx. 120° are designed for use in protected indoor areas. The scope of delivery includes the door, hinges and 2 keys.

Technical details

- Degree of protection: IP20
- Front door version: glass door, one-piece, with swing handle
- Design: Hinged door
- Transparent door version: Yes
- Front door opening angle: approx. 120 °
- Front door locking: 1-point pre-latch access
- Material: glass, side elements aluminium
- Finish of the surface: powder-coated aluminium elements
- Colour: black
- RAL number: 9005
- Width: 515 mm
- Height: 900.9 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

Fronttür für Wandgehäuse 691920TS.80, mit Scharnieren und Schloss

- For cabinet width: 600 mm
- Scope of delivery: door, incl. hinges, 2 x keys

Technical properties

Cabinet Series	Wall Housings 1/2-part
Degree of protection	IP20
Door opening angle	ca. 120 °
For Cabinet Width	600 mm
Material	Glass, side elements aluminium
Model	Stop door
Number of height units (U)	12
Profile half-cylinder exchangeable	False
Scope of delivery	Tür, inkl. Scharnieren, 2 x Schlüssel
Structure/Use	Glastür, einteilig, mit Schwenkhebel
Surface finishing	Aluminium elements powder-coated
Type of closure	Single-point latch locking
Version as glazed door	True

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	Depth	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
691912TS.TUR	Fronttür für Wandgehäuse 691912TS.80, mit Scharnieren und Schloss	600 mm	black	545.3 mm	515 mm	22 mm	9005	False	False
691916TS.TUR	Fronttür für Wandgehäuse 691916TS.80, mit Scharnieren und Schloss	600 mm	black	723.1 mm	515 mm	22 mm	9005	False	False
691920TS.TUR	Fronttür für Wandgehäuse 691920TS.80, mit Scharnieren und Schloss	600 mm	black	900.9 mm	515 mm	22 mm	9005	False	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Fronttür für Wandgehäuse 691920TS.80, mit Scharnieren und Schloss

691922TS.TUR	Fronttür für Wandgehäuse 691922TS.80, mit Scharnieren und Schloss	600 mm	black	989.9 mm	515 mm	22 mm	9005	False	False
691926TS.TUR	Fronttür für Wandgehäuse 691926TS.80, mit Scharnieren und Schloss	600 mm	black	1167.6 mm	515 mm	22 mm	9005	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

