

DATASHEET

Fronttür für Wandgehäuse 691922GR.80, mit Scharnieren und Schloss



General data

The front door for wall enclosures in grey RAL 7035 complements 600 mm cabinets with a closed, visibly controllable front. The one-piece glass design with hinges is designed for functional integration into existing enclosure concepts and combines a clear look with technical practicality.

- One-piece glass door with vision function – Allows control of the built-in components without additional opening of the housing.
- 1-point latch lock with swing handle – Ensures easy handling and a compact, well-defined lock.
- Designed for 600 mm wall-mounted enclosures in RAL 7035 – Fits into standardised cabinet designs and supports a uniform appearance.

In terms of technical design, the door combines a glass surface with aluminium side elements and is designed as a hinged door. With a width of 515 mm, a height of 989.9 mm and a depth of 22 mm, it is designed for wall enclosures with a cabinet width of 600 mm. The transparent door design supports visual inspection of the interior, while hinges and two keys are included in the scope of delivery to simplify installation.

Technical details

- Number of doors: 1
- Degree of protection: IP20
- With front door: Yes
- Front door version: glass door, one-piece, with swing handle
- Transparent door version: Yes
- Front door opening angle: approx. 120 °
- Front door locking: 1-point pre-latch access
- For cabinet width: 600 mm
- Colour: grey
- RAL number: 7035

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

Fronttür für Wandgehäuse 691922GR.80, mit Scharnieren und Schloss

- Width: 515 mm
- Height: 989.9 mm
- Depth: 22 mm
- Material: glass, side elements aluminium
- Scope of delivery: door, incl. hinges, 2 x keys

Technical properties

Cabinet Series	Wall Housings 1/2-part
Degree of protection	IP20
Door opening angle	ca. 120 °
For Cabinet Width	600 mm
Material	Glass, side elements aluminium
Model	Stop door
Number of height units (U)	12
Profile half-cylinder exchangeable	False
Scope of delivery	Tür, inkl. Scharnieren, 2 x Schlüssel
Structure/Use	Glastür, einteilig, mit Schwenkhebel
Surface finishing	Aluminium elements powder-coated
Type of closure	Single-point latch locking
Version as glazed door	True

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	Depth	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
691912GR.TUR	Fronttür für Wandgehäuse 691912GR.80, mit Scharnieren und Schloss	600 mm	grey	545.3 mm	515 mm	22 mm	7035	False	False
691916GR.TUR	Fronttür für Wandgehäuse 691916GR.80, mit Scharnieren und Schloss	600 mm	grey	723.1 mm	515 mm	22 mm	7035	False	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Fronttür für Wandgehäuse 691922GR.80, mit Scharnieren und Schloss

691920GR.TUR	Fronttür für Wandgehäuse 691920GR.80, mit Scharnieren und Schloss	600 mm	grey	900.9 mm	515 mm	22 mm	7035	False	False
691922GR.TUR	Fronttür für Wandgehäuse 691922GR.80, mit Scharnieren und Schloss	600 mm	grey	989.9 mm	515 mm	22 mm	7035	False	False
691926GR.TUR	Fronttür für Wandgehäuse 691926GR.80, mit Scharnieren und Schloss	600 mm	grey	1167.6 mm	515 mm	22 mm	7035	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

