DATASHEET

19“ Wall Housing 22U, Depth 800 mm, Pre-Assembled, RAL9005







General data

The 19-inch wall enclosure in 22 U and 800 mm depth in RAL 9005 is designed as a robust solution for demanding IT and network installations. The pre-assembled, dismountable sheet steel construction with bolted frame creates a stable basis for the installation and operation of the components.

• 22U at 800mm depth – Provides plenty of installation space in a well-defined 19" structure and supports clean integration of technology.
• Pre-assembled, dismountable sheet steel housing with bolted frame – Reduces assembly effort and ensures a resilient construction during operation.
• Front door with viewing window made of certified safety glass, 4 mm, and replaceable door hinge – facilitates visual inspection and adapts flexibly to the installation situation.

In terms of technical design, the enclosure combines a mounting level at the front and rear with passive ventilation and IP20 protection. The cable entry over the roof, floor and rear, each measuring 145 x 70 mm, supports clean cable routing. With a width of 600 mm, a height of 1078 mm, a powder-coated surface, earthing and a maximum load capacity of 80 kg, the wall-mounted enclosure is designed for use in controlled indoor areas.

Technical details
• Number of doors: 1

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19“ Wall Housing 22U, Depth 800 mm, Pre-Assembled, RAL9005

• Degree of protection: IP20
• Type of ventilation: passive
• Air inlet floor: roof + floor + back, each 145 x 70 mm
• With earthing: Yes
• With roof panel: Yes
• With front door: Yes
• With side panels: Yes, openable, lockable
• Mounting level: front and rear
• Front door design: glass door with latch lock and viewing window made of certified safety glass, 4 mm
• Front door locking: Latch lock
• Scope of delivery: 1x cabinet, 1x brush strip, 1x plastic cover for cable entry, 1x cage nut set (pack of 20 pcs.), 2x wrench
• Packaging: Delivered in transport packaging on a one-way pallet

Technical properties	
Cabinet Series	19" Wall Housing Depth 800 mm, pre-assembled
Cable entry roof/floor	Roof + base + back, each 145 x 70 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Frame	screwed together, pre-assembled, disassemblable
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
Number of doors	1
PHC replaceable front door	No
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover for cable entry, 1x cage nut set (Pack size 20 pieces), 2x keys
Structure/Use	Steel sheet housing with bolted frame, pre-assembled, self-ventilated, disassemblable.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	Crank
Type of ventilation	Passive
With earthing	True
With front door	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19“ Wall Housing 22U, Depth 800 mm, Pre-Assembled, RAL9005

With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Max. load capacity	Number of height units	Width	RAL-number
691912TS.80	19“ Wall Housing 12U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	634 mm	80 kg	80 kg	12 U	600 mm	7035
691916TS.80	19“ Wall Housing 16U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	812 mm	80 kg	80 kg	16 U	600 mm	7035
691920TS.80	19“ Wall Housing 20U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	990 mm	80 kg	80 kg	20 U	600 mm	7035
691922TS.80	19“ Wall Housing 22U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	1078 mm	80 kg	80 kg	22 U	600 mm	7035
691926TS.80	19“ Wall Housing 26U, Depth 800 mm, Pre-Assembled, RAL9005	black	800 mm	1256 mm	80 kg	80 kg	26 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product’s suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION