

DATASHEET

Fronttür für Wandgehäuse 691922TS.80, mit Scharnieren und Schloss



General data

The front door for wall enclosures in black RAL 9005 is designed as a one-piece glass element with swing handle. It combines visual inspection with a compact hinged door and is intended for cabinet widths of 600 mm. The design is adapted to the 22 U wall enclosure environment.

- One-piece glass element as a viewing door – Enables the components to be checked when closed and supports a quick overview during operation.
- 1-Point Latch Locking with Swing handle – Provides robust, practical locking and simplifies access for service and maintenance.
- Design for 600 mm cabinet width and 22 U – Ensures precise integration into suitable wall enclosures and reduces the coordination effort in the project.

In the technical construction, the door combines a width of 515 mm, a height of 989.9 mm and a depth of 22 mm with glass and side elements made of aluminium. The surface is powder-coated aluminium elements and the colour is black with RAL 9005. The door opening angle is approx. 120 °. The scope of delivery includes the door including hinges and 2 keys.

Technical details

- Degree of protection: IP20
- Front door version: glass door, one-piece, with swing handle
- Front door opening angle: approx. 120 °
- Front door locking: 1-point pre-latch access
- Scope of delivery: door, incl. hinges, 2 x keys
- Number of rack units (U): 22 U
- For cabinet width: 600 mm
- Colour: black
- RAL number: 9005

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Fronttür für Wandgehäuse 691922TS.80, mit Scharnieren und Schloss

- Material: glass, side elements aluminium
- Transparent door version: Yes
- Design: Hinged door
- Width: 515 mm
- Height: 989.9 mm
- Depth: 22 mm
- Cabinet Series: Wall Enclosure 1/2 Piece

Technical properties

Cabinet Series	Wall Housings 1/2-part
Degree of protection	IP20
Door opening angle	ca. 120 °
For Cabinet Width	600 mm
Material	Glass, side elements aluminium
Model	Stop door
Number of height units (U)	12
Profile half-cylinder exchangeable	False
Scope of delivery	Tür, inkl. Scharnieren, 2 x Schlüssel
Structure/Use	Glastür, einteilig, mit Schwenkhebel
Surface finishing	Aluminium elements powder-coated
Type of closure	Single-point latch locking
Version as glazed door	True

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	Depth	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
691912TS.TUR	Fronttür für Wandgehäuse 691912TS.80, mit Scharnieren und Schloss	600 mm	black	545.3 mm	515 mm	22 mm	9005	False	False
691916TS.TUR	Fronttür für Wandgehäuse 691916TS.80, mit Scharnieren und Schloss	600 mm	black	723.1 mm	515 mm	22 mm	9005	False	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Fronttür für Wandgehäuse 691922TS.80, mit Scharnieren und Schloss

691920TS.TUR	Fronttür für Wandgehäuse 691920TS.80, mit Scharnieren und Schloss	600 mm	black	900.9 mm	515 mm	22 mm	9005	False	False
691922TS.TUR	Fronttür für Wandgehäuse 691922TS.80, mit Scharnieren und Schloss	600 mm	black	989.9 mm	515 mm	22 mm	9005	False	False
691926TS.TUR	Fronttür für Wandgehäuse 691926TS.80, mit Scharnieren und Schloss	600 mm	black	1167.6 mm	515 mm	22 mm	9005	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

