


DATASHEET

19" Wall Housing 26U, Depth 800 mm, Pre-Assembled, RAL7035



General data

The 19-inch wall enclosure from EFB-Elektronik in RAL 7035 is designed as a robust, pre-assembled solution for demanding installation environments. With 26 U, 800 mm depth and bolted frame, it offers a stable basis for accommodating network and IT components.

- 26U in 482.6 mm pitch and 800 mm depth – Creates generous reserves for structured assembly with active and passive components.
- Pre-assembled, dismountable sheet steel construction with bolted frame – Facilitates transport, storage and assembly on site.
- Front door with viewing window made of certified safety glass and replaceable door hinge – Combines visual inspection with high adaptability to the installation situation.

The structural design relies on a powder-coated sheet steel design with passive ventilation and self-ventilated housing. The IP20 protection class and the load capacity of 80 kg are designed for use in controlled indoor areas. Cable entries over the roof, floor and rear with 145 x 70 mm each, as well as mounting levels at the front and rear, support a clean integration of the components. This is complemented by earthing, roof panel, front door and openable, lockable side panels.

Technical details

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing 26U, Depth 800 mm, Pre-Assembled, RAL7035

- Number of doors: 1
- Degree of protection: IP20
- Type of ventilation: passive
- Air inlet floor: roof + floor + back, each 145 x 70 mm
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, openable, lockable
- Mounting level: front and rear
- Front door version: glass door with latch lock and viewing window made of certified safety glass (4 mm)
- Front door locking: Latch lock
- Scope of delivery: 1x cabinet, 1x brush strip, 1x plastic cover for cable entry, 1x cage nut set (pack of 20 pcs.), 2x wrench
- Packaging: Delivered in transport packaging on a one-way pallet

Technical properties

Cabinet Series	19" Wall Housing Depth 800 mm, pre-assembled
Cable entry roof/floor	Roof + base + back, each 145 x 70 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes
Frame	screwed together, pre-assembled, disassemblable
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
Number of doors	1
PHC replaceable front door	No
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover for cable entry, 1x cage nut set (Pack size 20 pieces), 2x keys
Structure/Use	Steel sheet housing with bolted frame, pre-assembled, self-ventilated, disassemblable.
Surface finishing	Powder coating
Type of front door	Glass door with latch lock and viewing window made of certified safety glass (4 mm)
Type of profile rail	Crank
Type of ventilation	Passive
With earthing	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing 26U, Depth 800 mm, Pre-Assembled, RAL7035

With front door	True
With roof plate	True
With sidewall	Yes, can be opened and locked

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Max. load capacity	Number of height units	Width	RAL-number
691912GR.80	19" Wall Housing 12U, Fixed, Depth 800 mm, RAL7035	grey	800 mm	634 mm	80 kg	80 kg	12 U	600 mm	7035
691916GR.80	19" Wall Housing 16U, Depth 800 mm, Pre-Assembled, RAL7035	grey	800 mm	812 mm	80 kg	80 kg	16 U	600 mm	7035
691920GR.80	19" Wall Housing 20U, Depth 800 mm, Pre-Assembled, RAL7035	grey	800 mm	990 mm	80 kg	80 kg	20 U	600 mm	7035
691922GR.80	19" Wall Housing 22U, Depth 800 mm, Pre-Assembled, RAL7035	grey	800 mm	1078 mm	80 kg	80 kg	22 U	600 mm	7035
691926GR.80	19" Wall Housing 26U, Depth 800 mm, Pre-Assembled, RAL7035	grey	800 mm	1256 mm	80 kg	80 kg	26 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

