

# DATASHEET

## 19" 1U Lighting Unit "Basic LED"



### General data

Ready-to-connect lighting unit 19" 1U  
 For horizontal mounting in the 19" level of network and server cabinets  
 Operating voltage 100 .. 240 V AC, 8 W  
 This lighting unit contains a lighting source in energy efficiency class E  
 LED light colour warm-white, light output 800 Lm, Ra > 80  
 Materials holder stainless steel, body aluminium, cover plastic  
 Dimensions (WxHxD) 480 x 44 x 26 mm  
 Delivery incl. power cable 2 m white, with Euro plug and switch

### Technical properties

|                               |                |
|-------------------------------|----------------|
| Degree of protection          | IP20           |
| Lamp power                    | 8 W            |
| Magnetic mounting             | False          |
| Material                      | Aluminium      |
| Rated voltage                 | 240 V          |
| Type of electrical connection | Plug/connector |
| Type of lamp                  | LED            |
| With light sensor             | False          |
| With on/off switch            | True           |
| With socket outlet            | False          |

### Available variants

This datasheet was created automatically on 29-09-2026 . Technical changes reserved.



# DATASHEET

## 19" 1U Lighting Unit "Basic LED"

| ArtNr.   | Bezeichnung                      | Length |
|----------|----------------------------------|--------|
| 698023.3 | 19" 1U Lighting Unit "Basic LED" | 480 mm |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 29-09-2026 . Technical changes reserved.

