

DATASHEET

19" 1U Cable Routing Panel, 5 x Metal Double Bracket 75 mm, RAL7035



General data

For clear and orderly cable routing in the 19" level
 Especially solid steel double brackets, diameter 5 mm
 Bracket turnable in steps of 90°
 The cable brackets are included loose and still need to be snapped into the base plate.
 Bracket length 75 or 110 mm
 Material bracket + panel steel, holder PA
 Colour RAL7035, light grey / RAL9005, jet black

Technical properties

Cabinet Series	Universal
Category	Kabelführung
Material	Steel, polyamide
Model	Kabelführung
Number of brackets	5
Scope of delivery	1 x Grundplatte, 5 x Kabelbügel
Structure/Use	Zur geordneten und übersichtlichen Kabelführung an der 19" Ebene. Besonders stabile Stahl-Doppelbügel, Durchmesser 5 mm. Bügel in 90° Schritten drehbar. Hinweis: Lieferung erfolgt unmontiert.
Suitable for 19 inch mounting	True
Surface Finishing	pulverbeschichtet

Available variants

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

DATASHEET

19" 1U Cable Routing Panel, 5 x Metal Double Bracket 75 mm, RAL7035

ArtNr.	Bezeichnung	Bracket Length	Colour	Height	Length	Number of height units	RAL	Width
699981.1	19" 1U Cable Routing Panel, 5 x Metal Double Bracket 75 mm, RAL7035	75 mm	grey	44.45 mm	85 mm	1 U	7035	482.6 mm
699981.2	19" 1U Cable Routing Panel, 5 x Metal Double Bracket 110 mm, RAL7035	110 mm	grey	44.45 mm	120 mm	1 U	7035	482.6 mm
699981TS.1	19" 1U Cable Routing Panel, 5 x Metal Double Bracket 75 mm, RAL9005	75 mm	black	44.45 mm	85 mm	1 U	9005	482.6 mm
699981TS.2	19" 1U Cable Routing Panel, 5 x Metal Double Bracket 110 mm, RAL9005	110 mm	black	44.45 mm	120 mm	1 U	9005	482.6 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

