

# DATASHEET

## DisplayPort/HDMI Adapter 4K@60Hz



### General data

Adapter to connect DisplayPort graphic controller to HDMI displays  
 Supports 4k@ 60Hz resolution  
 One sided signal way DisplayPort => HDMI output device  
 DisplayPort v1.2 compliant  
 Supports HDCP 1.3 and DPCP  
 Colour: black

### Technical properties

|                                     |             |
|-------------------------------------|-------------|
| 3D                                  | False       |
| ARC                                 | True        |
| Backwards compatible                | True        |
| CEC                                 | False       |
| Cable set                           | False       |
| Cable type (passive/active/optical) | active      |
| Chip                                | True        |
| Compliant with                      | TV          |
| Connection type connection 1        | Plug        |
| Connection type connection 2        | plug        |
| Connector 1 angulation              | 180°        |
| Connector 2 angulation              | 180°        |
| Contact Plating                     | gold-plated |
| DSC                                 | False       |
| Dust cover                          | True        |
| HDCP Version                        | HDCP 2.2    |
| HDMI Power                          | False       |
| HDMI certified                      | True        |
| HEC (Ethernet channel)              | False       |
| Halogenfree                         | No          |
| Kink protection                     | False       |
| MSA                                 | False       |
| MST                                 | False       |
| Material Connector Housing          | Aluminium   |
| Material Inner Conductor            | BC          |
| Max. mating cycles                  | 5000        |
| Max. resolution                     | 4K@60Hz     |
| Model                               | Adapter     |

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.



# DATASHEET

## DisplayPort/HDMI Adapter 4K@60Hz

|                                |                                |
|--------------------------------|--------------------------------|
| Number of poles connection 1   | 20                             |
| Number of poles connection 2   | 19                             |
| Operating temperature          | -5 - 45 °C                     |
| PCIe Data transfer             | False                          |
| Scope of delivery              | 1xDP-HDMI Cable                |
| Shielded                       | True                           |
| Speed                          | 18 Gbit/s                      |
| Supported video standards      | 4K UHD - Ultra High Definition |
| Temperature                    | -20 - 70 °C                    |
| Type of connector connection 1 | DisplayPort (DP)               |
| Type of connector connection 2 | HDMI Type A                    |
| Type of locking                | Snap-in Locking                |
| Type of packaging              | plastic bag                    |
| Type of signal                 | Digital                        |
| VESA certified                 | False                          |
| VRR                            | False                          |
| Various lengths cable set      | 1                              |
| Version                        | HDMI Version 1.4               |
| Warranty                       | 36 months                      |
| With termination resistor      | False                          |
| eARC                           | False                          |

### Available variants

#### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.

