

DATASHEET

Inline-Closure for 24 splices



General data

Small Inline-closure for connecting and branching,
splice cassette and splice holder included in delivery

Technical properties

Cable Diameter	- 22 mm
Cable glands	4
Colour	black
Degree of protection	IP68
Design	Inline
Dimension (LxBxH)	369x182x106 mm
Direct Burial	True

This datasheet was created automatically on 09-09-2026 . Technical changes reserved.

DATASHEET

Inline-Closure for 24 splices

In-/Outputs	4
Lockable	False
Material	Plastic
Number of TPUs	1
Number of splice holders	2
Operating Temperature	-30 – 60 °C
Scope of delivery	1x sleeve incl. splice cassette
Sealing Type	Gel
Splice Cassette	integrated
Splice Cassettes (Number)	1
Splice Holder	crimp
Splice protection	Crimp/ANT
Standards	IEC 60529
Suitable for number of fibres	24
Type of closure	Junction closure
UV resistant	True

Available variants

ArtNr.	Bezeichnung	Unique
83127.1V2	Inline-Closure for 24 splices	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 09-09-2026 . Technical changes reserved.

