

DATASHEET

Outdoor Pipe Closure for 4x12 crimp splice /connecting or junction



General data

Outdoor Pipe Closure with 3 cable entries for junction or connecting of fiber optic cable. Including 4 splice holder **for up to 48 splices**

Features

Installation: direct burial in the ground

Material: Green Polypropylene (PP 4408) Housing

Seals made of thermoplastic elastomer and Sconablend

Optional accessories: **83189.3S** Key set for tightening the sleeve

Technical properties

Bending diameter fiber carrier

36 mm

This datasheet was created automatically on 17-10-2026 . Technical changes reserved.

DATASHEET

Outdoor Pipe Closure for 4x12 crimp splice /connecting or junction

Cable Diameter	2x 7-13. 1x 11-17 mm
Cable glands	2x M20 and 1x M25
Colour	Green
Degree of protection	IP68
Design	Socket cable connector
Diameter, housing	101 mm
Dimension (LxBxH)	360x101x101 mm
Direct Burial	True
In-/Outputs	3
Length of housing	360 mm
Material	Polypropylene
Max. Fiber storage length	180 mm
Number of splice holders	4
Operating Temperature	-30 - 65 °C
Scope of delivery	1x sleeve incl. splice cassette
Sealing Type	Sealing ring
Splice Cassette	integrated
Splice Cassettes (Number)	2
Splice Holder	crimp
Splice protection	Crimp/ANT
Standards	ÖNORM EN 60529:1991+A1:2000+A2:2013
Suitable for number of fibres	48
Tensile stress / compression	55 N
Type of closure	Junction closure
UV resistant	True

Available variants

ArtNr.	Bezeichnung	Unique
83189.3	Outdoor Pipe Closure for 4x12 crimp splice /connecting or junction	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-10-2026 . Technical changes reserved.

