DATASHEET

Coax Cable RG58 C/U, 50 Ohm black, PVC, 100m ring



General data

Coaxial cable for high frequent measured data and signals defined characteristic impedance and tight production tolerances in 50 Ohm. Also available as UL type. (91058.xUL)

Technical properties

Armouring	False
Colour outer sheath	black
Diameter inner conductor	19/0.19 mm
Diameter outer conductor	0.12 mm
Dielectric	Fully-PE
Halogen free (acc. EN 50267-2-2)	False
Inner conductor category	Class 5 = flexible
Inner conductor material	Copper
Material outer sheath	PVC
Operating temperature, fix	-20 – 75 °C
Operating temperature, flexible	-20 – 75 °C
Outer conductor material	Copper
Type of outer conductor	braiding

Available variants

ArtNr.	Bezeichnung	Characteristic impedance	Lenght	Outer diameter approx.
91058.100	Coax Cable RG58 C/U, 50 Ohm black, PVC, 100m ring	50 Ohm	100.0 m	5.1 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Coax Cable RG58 C/U, 50 Ohm black, PVC, 100m ring

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION