DATASHEET

Coax cable RG58 PVC UL, 50 Ohm L01020B0025, 100m bundle



General data

Coaxial high-frequency cable suitable for transmitting signals and data with definable characteristic impedances and narrow manufacturing tolerances in a 50 ohm version.

Technical properties

Armouring	False
Colour outer sheath	black
Diameter inner conductor	0.93 mm
Dielectric	PE
Inner conductor category	Class 5 = flexible
Inner conductor material	Copper
Material outer sheath	FRNC
Outer conductor material	Copper
Type of outer conductor	braiding

Available variants

ArtNr.	Bezeichnung	Characteristic impedance	Inner conductor surface	Lenght	Outer conductor surface	Weight	Outer diameter approx.
91058UL.1	Coax cable RG58 PVC UL, 50 Ohm L01020B0025, 100m bundle	50 Ohm	Tinned	100 m	Tinned	34 kg/km	4.9 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Coax cable RG58 PVC UL, 50 Ohm L01020B0025, 100m bundle

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION