DATASHEET

Coax Cable RG179B/U, 75 Ohm PTFE insulation

General data

Application in commercial electronics and high-frequency technology.
Cable according to MIL-C-17F and MIL-C-17G. 75 Ohm type

Technical properties

Armouring	False
Colour outer sheath	brown
Diameter inner conductor	7/0.102 mm
Diameter outer conductor	- mm
Dielectric	Fully-PE
Halogen free (acc. EN 50267-2-2)	False
Inner conductor category	Class 2 = stranded
Inner conductor material	CCS, silver-coated
Material outer sheath	PTFE
Operating temperature, fix	-70 – 200 °C
Operating temperature, flexible	-70 – 200 °C
Outer conductor material	Copper
Type of outer conductor	braiding

Available variants

ArtNr.	Bezeichnung	Characteristic impedance	Lenght	Outer diameter approx.
91079.1	Coax Cable RG179B/U, 75 Ohm PTFE insulation	75 Ohm	1.0 m	2.54 mm

Note on Intended Use

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Coax Cable RG179B/U, 75 Ohm PTFE insulation

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION