

DATASHEET

Modular Flat Cable 4-pole black, unshielded, 100 m reel



General data

According international standard

4-pole:

1=black, 2 =red, 3=green, 4=yellow

6-pole:

1=white, 2=black, 3=red, 4=green, 5=yellow, 6=blue

8-pole:

1=grey, 2=orange, 3=black, 4=red, 5=green, 6=yellow, 7=blue, 8=brown

Unshielded

Technical properties

Armouring	False
Circuit integrity	False
Conductor category	Class 2 = stranded
Core identification	Colour
Core insulation	Polypropylene (PP)
Diameter conductor	0.33 mm
Flame retardant	No
Halogen free (acc. EN 50267-2-2)	False
Longitudinal water blocking	False
Low smoke (acc. EN 61034-2)	False
Material outer sheath	Polyvinylchlorid (PVC)
Operating temperature, fix	60 - °C
Operating temperature, flexible	0 - 60 °C
Outdoor use permitted	False
Protective sheath	Other

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Modular Flat Cable 4-pole black, unshielded, 100 m reel

Radial water blocking	False
Screen over stranding	None
Screen over stranding element	without

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Number of cores	Outer diameter approx.
92804.100	Modular Flat Cable 4-pole black, unshielded, 100 m reel	black	4	2.5 x 5.0 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

