
DATASHEET

Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, green 100M



General data
DRAKA Patch cable UC300 HS26. Electrically and mechanically high-quality 300 MHz patch cable. Especially for application of class D.

Technical properties	
AWG-size	26/7
Armour	none
Bending radius (dynamic)	50 mm
Cable	IEC 61156-6
Cable silicone free	True
Cable structure	SF/UTP
Cable type	Draka UC300 HS26
Cabling standards	ISO/IEC 11801
Category	5e
Characteristic impedance	100 ± 5 Ohm
Conductor category	Class 2 = stranded
Conductor material	Copper, tinned

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, green 100M

Core identification	Colour
Core insulation	PVC
Coupling attenuation	≥ 75 dB
Diameter conductor	0.48 mm
Directive/Regulation	RoHS 2011/65/UE
Euro class	Eca
Flame retardant	acc. to EN 60332-1
Halogen free	acc. to EN 60754-1/2
Harmonised Standard	EN 50575
Installation standard	EN 50174
Insulation resistance (500V)	≥ 2000 MOhm/km
Loop resistance	260 Ohm/km
Low smoke	acc. to EN 61034
Material outer sheath	FRNC-B
Max. Freuqency	MHz MHz
NVP value	67 %
Nominal cross section conductor	0.16 mm²
Operating capacity	43 pF/km
Operating temperature, fix	-20 – 60 °C
Operating temperature, flexible	0 – 50 °C
Operating temperature, storage	-20 – 60 °C
PoE	acc. to IEEE802.3af PoE
Resistance unbalance	3 %
Screen over stranding	foil + braid
Screen over stranding element	without
Separation class acc. EN50174-2	C
Stranding element	Pairs
Test voltage DC, 1 min	1000 V
Transmission standards	IEEE 802.3 10Mbit bis 2.5Gbit
UV resistant	Nein

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Number of cores	Type	Copper weight	Weight	Max. tractive force	Outer diameter approx.	Fire load

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, green 100M

99253.1	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, green	green	1.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99253.100	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, green 100M	green	100.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99253.1000	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, green	green	1000.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99254.1	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, blue	blue	1.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99254.100	Patch C. Cat.5E Draka SF/UTP AWG26 300MHz, blue 100M	blue	100.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99254.1000	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, blue	blue	1000.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99255.1	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz,yellow	yellow	1.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99255.1000	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, yellow	yellow	1000.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99256.1	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, red	red	1.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99256.1000	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, red	red	1000.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99258.1	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, grey	grey	1.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, green 100M

99258.100	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, grey 100m	grey	100.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99258.1000	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, grey	grey	1000.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km
99259.1000	Patch C. Cat.5E Draka SF/UTP AWG26, 300MHz, black	black	1000.0 m	8	simplex	22.5 kg/km	37 kg/km	100 N	5.7 mm	369 MJ/km

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION