DATASHEET

PATCH PRO FLEX CAT 7 Kabel PUR/Gummi, RAL9005, UV best., 100m



General data

The EFB-Elektronik Cat.7 flex cable with S/FTP design in black is designed for high-performance network cabling. The PUR sheathing in RAL 9005 supports a robust design for modern installations with high bandwidth and flexible routing. With a transmission frequency of up to 1000 MHz, the cable is suitable for demanding networks with corresponding power requirements.

• 1000 MHz Cat.7 bandwidth – Supports transmission standards from IEEE 802.3 10Mbit to 10Gbit and creates reserves for high-performance networks.
• S/FTP design with braid shielding – Reduces interference and supports stable signal quality in demanding cabling.
• Polyurethane (PUR) sheath in black according to RAL 9005 – Provides a robust sheath for flexible installations and is UV resistant.

The cable is designed as a simplex and uses 26/7 conductors with 8 wires. The dynamic bending radius of 40 mm facilitates installation in narrow routes. The braided shielding supports decoupling from external influences and the design is intended for PoE according to IEEE802.3af, PoE+ according to IEEE802.3at and 4PPoE according to IEEE802.3bt. The version without reinforcement is aimed at structured network environments and the regulation RoHS 2011/65/UE is met.

Technical details

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

PATCH PRO FLEX CAT 7 Kabel PUR/Gummi, RAL9005, UV best., 100m

- Brand: EFB-Elektronik
- Category: 7
- Transmission standards: IEEE 802.3 10Mbit to 10Gbit
- Max. frequency: 1000 MHz
- Cable construction: S/FTP
- PoE: after IEEE802.3af PoE, after IEEE802.3at PoE+, after IEEE802.3bt 4PPoE
- AWG cross-section/number of wires: 26/7
- Number of cores: 8
- Type: simplex
- Sheath material: polyurethane (PUR)
- Sheath colour: black
- RAL colour: RAL 9005
- Armour: without
- Bend radius (dynamic): 40 mm
- Directive/Regulation: RoHS 2011/65/UE
- UV resistant: Yes
- Shield over stranding: braid

Technical properties	
AWG-size	26/7
Armour	none
Bending radius (dynamic)	40 mm
Cable	IEC 61156-6
Cable silicone free	True
Cable structure	S/FTP
Cable type	Draka Patch Pro Flex Cat7
Cabling standards	ISO/IEC 11801
Category	7
Characteristic impedance	100 ± 5 Ohm
Conductor category	Class 2 = stranded
Conductor material	Copper, bare
Core identification	Colour
Core insulation	Foam-Skin-PE
Coupling attenuation	≥ 80 dB
Diameter conductor	0.48 mm
Directive/Regulation	RoHS 2011/65/UE
Euro class	none
Flame retardant	No
Halogen free	False
Harmonised Standard	EN 50575

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

PATCH PRO FLEX CAT 7 Kabel PUR/Gummi, RAL9005, UV best., 100m

Installation standard	EN 50174
Insulation resistance (500V)	≥ 2000 MOhm/km
Loop resistance	250 Ohm/km
Low smoke	nein
Material outer sheath	Polyurethan (PUR)
Max. Freuqency	MHz MHz
NVP value	75 %
Nominal cross section conductor	0.16 mm²
Operating capacity	43 pF/km
Operating temperature, fix	-20 – 60 °C
Operating temperature, flexible	0 – 50 °C
Operating temperature, storage	-20 – 60 °C
PoE	acc. to IEEE802.3af PoE
Resistance unbalance	2 %
Screen over stranding	braiding
Screen over stranding element	Foil
Stranding element	Pairs
Test voltage DC, 1 min	1000 V
Transmission standards	IEEE 802.3 10Mbit bis 10Gbit
UV resistant	True

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Number of cores	RAL colour	Type	Copper weight	Weight	Max. tractive force	Outer diameter approx.	Fire load
99262.1	PATCH PRO FLEX CAT 7 Kabel PUR/Gummi, RAL9005, UV best.	black	1.0 m	8	RAL 9005	simplex	17.5 kg/km	35 kg/km	100 N	6.4 mm	688 MJ/km
99262.100	PATCH PRO FLEX CAT 7 Kabel PUR/Gummi, RAL9005, UV best., 100m	black	100.0 m	8	RAL 9005	simplex	17.5 kg/km	35 kg/km	100 N	6.4 mm	688 MJ/km

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

PATCH PRO FLEX CAT 7 Kabel PUR/Gummi, RAL9005, UV best., 100m

99262.1000	PATCH PRO FLEX CAT 7 Cable PUR/Gummi, RAL9005, UV best.	black	1000.0 m	8	RAL 9005	simplex	17.5 kg/km	35 kg/km	100 N	6.4 mm	688 MJ/km
99262.500	PATCH PRO FLEX CAT 7 Kabel PUR/Gummi, RAL9005, UV best., 500m	black	500.0 m	8	RAL 9005	simplex	17.5 kg/km	35 kg/km	100 N	6.4 mm	688 MJ/km

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION