DATASHEET

Draka GreenConnect Cat.7 Outdoor Cable S/FTP PE,black, CPR Fca

General data

The DRAKA GreenConnect Cat.7 Outdoor Cable S/FTP PE in black is designed for high-performance network cabling outdoors. The S/FTP structure with PE jacket supports stable data connections up to 900 MHz and is therefore suitable for modern installations with high bandwidth. The UV resistance complements the design for outdoor use.

• 900 MHz Cat.7 bandwidth – Supports IEEE 802.3 10Mbit to 10Gbit and creates scope for high-performance network links.
• S/FTP setup with braid shielding – Reduces interference and supports stable signal quality in demanding outdoor installations.
• Polyethylene sheath in black with UV resistance – Designed for outdoor use and adds robust material properties to the installation.

The cable is designed as a simplex and uses 23/1 conductors with 8 wires. The dynamic bending radius of 80 mm facilitates installation. The braided shielding supports decoupling from external influences. The structure is intended for PoE according to IEEE802.3af, PoE+ according to IEEE802.3at and 4PPoE according to IEEE802.3bt. The version without reinforcement is aimed at structured outdoor cabling.

Technical details
• Brand: DRAKA
• Category: Cat.7

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Draka GreenConnect Cat.7 Outdoor Cable S/FTP PE,black, CPR Fca

- Transmission standards: IEEE 802.3 10Mbit to 10Gbit
- Max. frequency: 900 MHz
- Cable construction: S/FTP
- PoE: after IEEE802.3af PoE, after IEEE802.3at PoE+, after IEEE802.3bt 4PPoE
- AWG cross-section/number of wires: 23/1
- Number of cores: 8
- Type: simplex
- Sheath material: polyethylene (PE)
- Sheath colour: black
- Armour: without
- Bend radius (dynamic): 80 mm
- Directive/Regulation: RoHS 2011/65/UE
- UV resistant: Yes
- Shield over stranding: braid

Technical properties	
AWG-size	23/1
Armour	none
Bending radius (dynamic)	80 mm
Cable	EN 50288-4-1 900
Cable silicone free	True
Cable structure	S/FTP
Cable type	Draka GreenConnect Cat.7 PE
Cabling standards	ISO/IEC 11801
Category	7
Characteristic impedance	100 ± 5 Ohm
Conductor category	Class 1 = solid
Conductor material	Copper, bare
Core identification	Colour
Core insulation	Foam-Skin-PE
Coupling attenuation	≤ 85 dB
Diameter conductor	0.56 mm
Directive/Regulation	RoHS 2011/65/UE
Euro class	none
Flame retardant	No
Halogen free	False
Harmonised Standard	EN 50575
Installation standard	EN 50174
Insulation resistance (500V)	≥ 5000 MOhm/km

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Draka GreenConnect Cat.7 Outdoor Cable S/FTP PE,black, CPR Fca

Loop resistance	165 Ohm/km
Low smoke	nein
Material outer sheath	Polyethylene (PE)
Max. Freuqency	MHz MHz
NVP value	79 %
Nominal cross section conductor	0.26 mm²
Operating capacity	43 pF/km
Operating temperature, fix	-55 – 60 °C
Operating temperature, flexible	-20 – 50 °C
Operating temperature, storage	-20 – 60 °C
PoE	acc. to IEEE802.3af PoE
Resistance unbalance	2 %
Screen over stranding	braiding
Screen over stranding element	Foil
Separation class acc. EN50174-2	D
Stranding element	Pairs
Test voltage DC, 1 min	1000 V
Transmission standards	IEEE 802.3 10Mbit bis 10Gbit
UV resistant	True

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Number of cores	Type	Copper weight	Weight	Max. tractive force	Outer diameter approx.
99731GC.500	Draka GreenConnect Cat.7 Outdoor Cable S/FTP PE,black, CPR Fca	black	500.0 m	8	simplex	38 kg/km	64.6 kg/km	340 N	8.4 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION