DATASHEET

Patchkabel UC900M SS26 4P PUR red 100m ring

General data

The Cat.7 patch cable DRAKA UC900M SS26 4P with PUR jacket in red is designed for high-performance network cabling. The S/FTP design with braided shielding supports stable data connections up to 1000 MHz and is therefore suitable for modern installations with high bandwidth.

• 1000 MHz Cat.7 bandwidth – Supports transmission standards from IEEE 802.3 10Mbit to 10Gbit and creates scope for high-performance networks.
• S/FTP design with braid shielding – Reduces interference and supports stable signal quality in demanding cabling.
• Polyurethane (PUR) sheath in red – Adds clear colour coding and a suitable finish for structured network environments to the installation.

The patch cable is designed as a simplex and uses 26/7 conductors with 8 wires. The dynamic bending radius of 50 mm makes installation easier. The braided shielding supports decoupling from external influences and the structure is intended for PoE according to IEEE802.3af, PoE+ according to IEEE802.3at and 4PPoE according to IEEE802.3bt. The polyurethane (PUR) sheath is halogen-free according to EN 50267-1 and complies with RoHS 2011/65/UE. There is no reinforcement.

Technical details
• Brand: DRAKA
• Category: Cat.7
• Transmission standards: IEEE 802.3 10Mbit to 10Gbit
• Max. frequency: 1000 MHz
• Cable construction: S/FTP
• PoE: after IEEE802.3af PoE, after IEEE802.3at PoE+, after IEEE802.3bt 4PPoE
• AWG cross-section/number of wires: 26/7
• Number of cores: 8
• Type: simplex
• Sheath material: polyurethane (PUR)
• Sheath colour: red
• Armour: without
• Bend radius (dynamic): 50 mm
• Directive/Regulation: RoHS 2011/65/UE
• Halogen-free: according to EN 50267-1
• Shield over stranding: braid

Technical properties

AWG-size	26/7
Armour	none

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Patchkabel UC900M SS26 4P PUR red 100m ring

Bending radius (dynamic)	50 mm
Cable	IEC 61156-6
Cable silicone free	True
Cable structure	S/FTP
Cable type	Draka UC900 SS26 Cat.7 PUR
Cabling standards	ISO/IEC 11801
Category	7
Characteristic impedance	100 ± 5 Ohm
Conductor category	Class 2 = stranded
Conductor material	Copper, bare
Core identification	Colour
Core insulation	Foam-Skin PP
Coupling attenuation	≥ 80 dB
Diameter conductor	0.48 mm
Directive/Regulation	RoHS 2011/65/UE
Euro class	none
Flame retardant	acc. to EN 60332-1
Halogen free	acc. to EN 50267-1
Harmonised Standard	EN 50575
Installation standard	EN 50174
Insulation resistance (500V)	≥ 2000 MOhm/km
Loop resistance	290 Ohm/km
Low smoke	acc. to EN 61034
Material outer sheath	Polyurethan (PUR)
Max. Freuqency	MHz MHz
NVP value	79 %
Nominal cross section conductor	0.16 mm²
Operating capacity	43 pF/km
Operating temperature, fix	-30 – 75 °C
Operating temperature, flexible	0 – 50 °C
Operating temperature, storage	-20 – 60 °C
PoE	acc. to IEEE802.3af PoE
Resistance unbalance	3 %
Screen over stranding	braiding
Screen over stranding element	Foil
Separation class acc. EN50174-2	C
Stranding element	Pairs

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Patchkabel UC900M SS26 4P PUR red 100m ring

Test voltage DC, 1 min	1000 V
Transmission standards	IEEE 802.3 10Mbit bis 10Gbit
UV resistant	Nein

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Number of cores	Type	Copper weight	Weight	Max. tractive force	Outer diameter approx.	Fire load
99760.1	Patch cable UC900M SS26 4P PUR red	red	1.0 m	8	simplex	18 kg/km	38 kg/km	100 N	6.0 mm	565 MJ/km
99760.100	Patchkabel UC900M SS26 4P PUR red 100m ring	red	100.0 m	8	simplex	18 kg/km	38 kg/km	100 N	6.0 mm	565 MJ/km
99760.1000	Patch cable UC900M SS26 4P PUR red	red	1000.0 m	8	simplex	18 kg/km	38 kg/km	100 N	6.0 mm	565 MJ/km

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION