DATASHEET

Splice box gy fixed ST MM 24x simplex adapter



General data

Partly assembled splice box with adapters
per 12 adapters 1 splice cassette with 1 splice holder
suitable up to 4 splice cassettes
metal housing **depth adjustable**
front panel screwed
coloured adapters
cable entries at the rear

Technical properties

Adapters	ST
Depth	244.0 mm
Fibre type	Multi mode 50/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Sliding	non sliding version
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Splice box gy fixed ST MM 24x simplex adapter

B60003.24	Splice box gy fixed ST MM 24x simplex adapter	grey	24	ST	24	7035	ST	metal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION