

DATASHEET

Splicebox bk partially assembled LC MM extendable 16 Adapter



General data

Partly assembled splice box with adapters
per 12 adapters 1 splice cassette with 1 splice holder
suitable up to 4 splice cassettes
metal housing sliding unit
front panel screwed
metal adapters
cable entries at the rear

Technical properties

Adapters	LC-Duplex
Depth	244.0 mm
Fibre type	Multi mode 50/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Sliding	sliding version
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
--------	-------------	--------	---	----------------------------------	--------------------------------------	------------	----------------------------------	-------------------

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

Splicebox bk partially assembled LC MM extendable 16 Adapter

B61902.6	Splicebox partially assembled LC MM extendable 6 Adapter	grey	12	LC-Duplex	6	7035	LC-Duplex	metal
B61902TS.16	Splicebox bk partially assembled LC MM extendable 16 Adapter	Black	24	LC-Duplex	16	7035	LC-Duplex	metal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

