

DATASHEET

Splice box gy sliding LC OS2 6x duplex adapter



General data

Partly assembled splice box with adapters
per 12 adapters 1 splice cassette with 1 splice holder
suitable up to 4 splice cassettes
metal housing sliding unit
front panel screwed
plastic adapters
cable entries at the rear

Technical properties

Adapters	LC-Duplex
Depth	244.0 mm
Fibre class	OS2 acc. to ITU-T G.652.D
Fibre type	Single mode 9/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Sliding	sliding
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
--------	-------------	--------	---	----------------------------------	--------------------------------------	------------	----------------------------------	-------------------

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

Splice box gy sliding LC OS2 6x duplex adapter

B61921.12	Splice box gy sliding LC OS2 12x duplex adapter	grey	12	LC-Duplex	12	7035	LC-Duplex	blue
B61921.24	Splice box gy sliding LC OS2 24x duplex adapter	grey	24	LC-Duplex	24	7035	LC-Duplex	blue
B61921.6	Splice box gy sliding LC OS2 6x duplex adapter	grey	12	LC-Duplex	6	7035	LC-Duplex	blue
B61921TS.12	Splice box bk sliding LC OS2 12x duplex adapter	black	12	LC-Duplex	12	9005	LC-Duplex	blue
B61921TS.24	Splice box bk sliding LC OS2 24x duplex adapter	black	24	LC-Duplex	24	9005	LC-Duplex	blue

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

