



DATASHEET

Partially Assembled Breakoutbox with 4 LC-Duplex adapter OM3



General data

Partially assembled Breakout box equipped with LC duplex adapter

OM3

Front panel screwed and adapters inserted

Metal box

Technical properties

Adapter material	Plastic adapter
Depth	170 mm
Fibre class	OM3
Fibre type	Multi mode 50/125
Height	44 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Sliding	non sliding version

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Partially Assembled Breakoutbox with 4 LC-Duplex adapter OM3

Width	482 mm
With front plate	True
With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
B65901.12OM3	Partially Assembled Breakoutbox with 12 LC-Duplex adapter OM3	grey	12	LC-Duplex	12	7035	LC-Duplex	aqua
B65901.24OM3	Partially Assembled Breakoutbox with 24 LC-Duplex adapter OM3	grey	24	LC-Duplex	24	7035	LC-Duplex	aqua
B65901.2OM3	Partially Assembled Breakoutbox with 2 LC-Duplex adapter OM3	grey	2	LC-Duplex	2	7035	LC-Duplex	aqua
B65901.3OM3	Partially Assembled Breakoutbox with 3 LC-Duplex adapter OM3	grey	3	LC-Duplex	3	7035	LC-Duplex	aqua
B65901.4OM3	Partially Assembled Breakoutbox with 4 LC-Duplex adapter OM3	grey	4	LC-Duplex	4	7035	LC-Duplex	aqua
B65901.6OM3	Breakout box gy LC OM3 6x duplex adapter	grey	6	LC-Duplex	6	7035	LC-Duplex	aqua

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Partially Assembled Breakoutbox with 4 LC-Duplex adapter OM3

B65901.8OM3	Partially Assembled Breakoutbox with 8 LC-Duplex adapter OM3	grey	8	LC-Duplex	8	7035	LC-Duplex	aqua
-------------	--	------	---	-----------	---	------	-----------	------

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

