

DATASHEET

Splicebox ST 9/125μ OS2 not extendable 12 Pigtails/12 Adapter



General data

completely assembled splice box with adapters
and coloured pigtails
metal housing depth adjustable
cable entries at the rear, incl. 1 x PG16
6 x self adhesive fiber tray

Special assembly possible at short notice!

Technical properties

Adapter material	Metall adapter
Adapters	ST
Depth	244.0 mm
Fibre class	OS2 acc. to ITU-T G.652.D
Fibre type	Single mode 9/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	not stripped
Sliding	non sliding version
Width	483.0 mm

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

DATASHEET

Splicebox ST 9/125μ OS2 not extendable 12 Pigtails/12 Adapter

With front plate	True
With housing	True
With pigtails	True

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
B70023.12	Splicebox ST 9/125μ OS2 not extendable 12 Pigtails/12 Adapter	grey	12 x ST	12	ST	12	7035	ST	metal
B70023.24	Splicebox ST 9/125μ OS2 not extendable 24 Pigtails/24 Adapter	grey	24 x ST	24	ST	24	7035	ST	metal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

