

DATASHEET

Splice box gy fixed SC OS2 12x pigtail & 6x duplex adapter



General data

completely assembled splice box with adapters
and coloured pigtails
metal housing depth adjustable **cable entries at the rear, incl. 1 x PG16**
6 x self adhesive fiber tray
Special assembly possible at short notice!

Technical properties

Adapter material	Plastic adapter
Adapters	SC-Duplex
Depth	244.0 mm
Fibre class	OS2 acc. to ITU-T G.652.D
Fibre type	Single mode 9/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	not stripped
Sliding	non sliding version
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	True

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

Splice box gy fixed SC OS2 12x pigtail & 6x duplex adapter

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
B70223.12	Splice box gy fixed SC OS2 12x pigtail & 6x duplex adapter	grey	12 x SC	12	SC-Duplex	6	7035	SC-duplex	blue
B70223.24	Splice box gy fixed SC OS2 24x pigtail & 12x duplex adapter	grey	24 x SC	12	SC-Duplex	12	7035	SC-duplex	blue
B70223.48	Splice box gy fixed SC OS2 48x pigtail & 24x duplex adapter	grey	48 x SC	24	SC-Duplex	24	7035	SC-duplex	blue

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

