

DATASHEET

Splice box gy sliding ST OS2 12x pigtail and 12x simplex adapter



G657A1



General data

completely assembled splice box with adapters
and coloured pigtails
metal housing depth adjustable
cable entries at the rear, incl. 1 x PG16
6 x self adhesive fiber tray

Special assembly possible at short notice!

Technical properties

Adapter material	Metall adapter
Adapters	ST
Depth	244.0 mm
Fibre class	OS2 acc. to ITU-T G.652.D
Fibre type	Single mode 9/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	not stripped
Sliding	sliding version

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.



DATASHEET

Splice box gy sliding ST OS2 12x pigtail and 12x simplex adapter

Width	483.0 mm
With front plate	True
With housing	True
With pigtails	True

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
B71023.12	Splice box gy sliding ST OS2 12x pigtail and 12x simplex adapter	grey	12 x ST	12	ST	12	7035	ST	metal
B71023.24	Splice box gy sliding ST OS2 24x pigtail and 24x simplex adapter	grey	24 x ST	24	ST	24	7035	ST	metal
B71023.6	Splicebox ST 9/125µ OS2 extendable 6 Pigtails/6 Adapter	grey	6 x ST	12	ST	6	7035	ST	metal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.

