

DATASHEET

Splice box gy sliding SC OM5 12x pigtail and 6x duplex adapter



General data

- 1 splice cassette with 1 splice holder each per 12 fiber pigtails
- 6 x Self adhesive fiber tray
- Up to 4 splice cassettes adaptable
- Front panel screwed
- Depth adjustable
- Cable entry backsided, with 1 x PG16 gland
- Coloured Adapter

Technical properties

Adapters	SC-Duplex
Depth	244.0 mm
Fibre class	OM5
Fibre type	Multi mode 50/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	not stripped
Sliding	sliding version
Suitable for number of module inserts	4
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	True

This datasheet was created automatically on 02-10-2026 . Technical changes reserved.



DATASHEET

Splice box gy sliding SC OM5 12x pigtail and 6x duplex adapter

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
B71203.12OM5	Splice box gy sliding SC OM5 12x pigtail and 6x duplex adapter	grey	12 x SC	12	SC	6	7035	SC-Duplex	lime green
B71203.24OM5	Splice box gy sliding SC OM5 24x pigtail and 12x duplex adapter	grey	24 x SC	24	SC	12	7035	SC-Duplex	lime green
B71203.48OM5	Splice box gy sliding SC OM5 48x pigtail and 24x duplex adapter	grey	48 x SC	48	SC	24	7035	SC-Duplex	lime green

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 02-10-2026 . Technical changes reserved.

