DATASHEET


Splice box gy sliding SC OS2 48x pigtail and 24x duplex adapter











General data

completely assembled splice box with adapters
and coloured pigtails
metal housing depth adjustable**cable entries at the rear, incl. 1 x PG16**
6 x self adhesive fiber tray
Special assembly possible at short notice!

Technical properties

Adapter material	Plastic adapter
Adapters	SC-Duplex
Depth	244.0 mm
Fibre class	OS2 acc. to ITU-T G.652.D
Fibre type	Single mode 9/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	not stripped
Sliding	sliding
Width	483.0 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Splice box gy sliding SC OS2 48x pigtail and 24x duplex adapter

With front plate	True
With housing	True
With pigtails	True

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
B71223.12	Splice box gy sliding SC OS2 12x pigtail and 6x duplex adapter	grey	12 x SC	12	SC-Duplex	6	7035	SC-duplex	blue
B71223.48	Splice box gy sliding SC OS2 48x pigtail and 24x duplex adapter	grey	48 x SC	24	SC-Duplex	24	7035	SC-duplex	blue
B71228.12	Splice box gy sliding SC/APC 12x pigtail and 6x duplex adapter	grey	12 x SC/APC	12	SC-Duplex	12	7035	SC-duplex	green
B71228.24	Splice box gy sliding SC/APC 24x pigtail and 24x simplex adapter	grey	24 x SC-APC	12	SC-Duplex	24	7035	SC-duplex	green
B71228.48	Splice box gy sliding SC/APC 48x pigtail and 24x duplex adapter	grey	48 x SC-APC	24	SC-Duplex	48	7035	SC-duplex	green

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.