


DATASHEET

Splice box gy sliding LC OM4 12x pigtail and 6x duplex adapter



General data

completely assembled splice box with adapters and coloured pigtails

metal housing depth adjustable

cable entries at the rear, incl. 1 x PG16

6 x self adhesive fiber tray

Special assembly possible at short notice!

Technical properties

Adapter material	Plastic adapter
Adapters	LC-Duplex
Depth	244.0 mm
Fibre class	OM4
Fibre type	Multi mode 50/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	not stripped
Sliding	sliding version
Width	483.0 mm

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.

DATASHEET

Splice box gy sliding LC OM4 12x pigtail and 6x duplex adapter

With front plate	True
With housing	True
With pigtails	True

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
B71901.12OM4	Splice box gy sliding LC OM4 12x pigtail and 6x duplex adapter	grey	12 x LC	12	LC-Duplex	6	7035	LC-Duplex	Violet
B71901.24OM4	Splice box gy sliding LC OM4 24x pigtail and 12x duplex adapter	grey	24 x LC	12	LC-Duplex	12	7035	LC-Duplex	Violet
B71901.48OM4	Splice box gy sliding LC OM4 48x pigtail and 24x duplex adapter	grey	48 x LC	24	LC-Duplex	24	7035	LC-Duplex	Violet
B71901TS.48OM4	Splice box bk sliding LC OM4 48x pigtail & 24x duplex adapter	Black	48 x LC	24	LC-Duplex	24	9005	LC-Duplex	violet

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.

