# DATASHEET

## Drawing-In Tube with M40 screwing, 1,5m, for 25-48 connector



### General data

Line outside diameter max. 6-15 mm, solid, flexible plastic tube
Outside diameter 40 mm
Reusable

### Technical properties

### Available variants

| ArtNr. | Bezeichnung | Number of fibres | With hollow cable | Material | Cable strain relief |
|---|---|---|---|---|---|
| B9000.1 | Drawing-In Tube with PG screwing, 1m | 24 | False | plastic | True |
| B9000.1,5 | Drawing-In Tube with M40 screwing, 1,5m, for 25-48 connector | 48 | False | plastic | True |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION