

DATASHEET

Splice box gy sliding SC OM3 24x fanout pigtail and 12x duplex adapter



General data

completely assembled splice box with adapters and coloured pigtails.
metal housing depth adjustable
cable entries at the rear, incl. 1 x PG16
6 x self adhesive fiber tray
Special assembly possible at short notice!

Technical properties

Adapter material	Plastic adapter
Adapters	SC-Duplex
Depth	244.0 mm
Fibre class	OM3
Fibre type	Multi mode 50/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	stripped
Sliding	sliding version
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	True

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.

DATASHEET

Splice box gy sliding SC OM3 24x fanout pigtail and 12x duplex adapter

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
BA71203.12OM3	Splice box gy sliding SC OM3 12x fanout pigtail and 6x duplex adapter	grey	12 x SC	12	SC-Duplex	6	7035	SC-duplex	aqua
BA71203.24OM3	Splice box gy sliding SC OM3 24x fanout pigtail and 12x duplex adapter	grey	24 x SC	12	SC-Duplex	12	7035	SC-duplex	aqua
BA71203.48OM3	Splice box gy sliding SC OM3 48x fanout pigtail and 24x duplex adapter	grey	48 x SC	48	SC-Duplex	24	7035	SC-duplex	aqua

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.

