


DATASHEET

Splice box gy sliding E2000 OS2 24x fanout pigtail and 24x simplex adapter



General data

completely assembled splice box with adapters and coloured pigtails
metal housing depth adjustable
cable entries at the rear, incl. 1 x PG16
6 x self adhesive fiber tray

Special assembly possible at short notice!

Technical properties

Adapter material	Plastic adapter
Adapters	E2000®
Depth	244.0 mm
Fibre class	OS2 acc. to ITU-T G.652.D
Fibre type	Singlemode 9/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	stripped
Sliding	sliding version
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	True

This datasheet was created automatically on 10-10-2026 . Technical changes reserved.

DATASHEET

Splice box gy sliding E2000 OS2 24x fanout pigtail and 24x simplex adapter

Available variants									
ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
BA71523.12	Splice box gy sliding E2000 OS2 12x fanout pigtail and 12x simplex adapter	grey	12 x E2000®	12	E2000®	12	7035	E2000®	blue
BA71523.24	Splice box gy sliding E2000 OS2 24x fanout pigtail and 24x simplex adapter	grey	24 x E2000®	24	E2000®	24	7035	E2000®	blue
BA71533.12	Splice box gy sliding E2000/APC OS2 12x fanout pigtail and 12x simplex adapter	grey	12 x E2000®/APC	12	E2000®	12	7035	E2000®	green
BA71533.24	Splice box gy sliding E2000/APC OS2 24x fanout pigtail and 24x simplex adapter	grey	24 x E2000®/APC	24	E2000®	24	7035	E2000®	green
BA71533.6	Splice box gy sliding E2000/APC OS2 6x fanout pigtail and 6x simplex adapter	grey	6 x E2000®/APC	6	E2000®	6	7035	E2000®	green
BA71533TS.12	Splice box bk sliding E2000/APC OS2 12x fanout pigtail & 12x simplex adapter	Black	12 x E2000®/APC	12	E2000®	12	9005	E2000®	green

This datasheet was created automatically on 10-10-2026 . Technical changes reserved.



DATASHEET

Splice box gy sliding E2000 OS2 24x fanout pigtail and 24x simplex adapter

BA71533TS.24	Splice box bk sliding E2000/APC OS2 24x fanout pigtail & 24x simplex adapter	Black	24 x E2000®/APC	24	E2000®	24	9005	E2000®	green
--------------	--	-------	-----------------	----	--------	----	------	--------	-------

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 10-10-2026 . Technical changes reserved.

