

DATASHEET

Splicebox LC 50/125μ OM2 extendable 12 Pigtails stripped/6 Adapter



General data

completely assembled splice box with adapters and coloured pigtails
metal housing depth adjustable
cable entries at the rear, incl. 1 x PG16
6 x self adhesive fiber tray

Special assembly possible at short notice!

Technical properties

Adapter material	Metall adapter
Adapters	LC-Duplex
Depth	244.0 mm
Fibre class	OM2
Fibre type	Multimode 50/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	stripped
Sliding	sliding version
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	True

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

DATASHEET

Splicebox LC 50/125μ OM2 extendable 12 Pigtails stripped/6 Adapter

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
BA71902.12	Splicebox LC 50/125μ OM2 extendable 12 Pigtails stripped/6 Adapter	grey	12 x LC	12	LC-Duplex	6	7035	LC-Duplex	metal
BA71902.24	Splicebox LC 50/125μ OM2 extendable 24 Pigtails stripped/12 Adapter	grey	24 x LC	12	LC-Duplex	12	7035	LC-Duplex	metal
BA71902.48	Splicebox LC 50/125μ OM2 extendable 48 Pigtails stripped/24 Adapter	grey	48 x LC	24	LC-Duplex	24	7035	LC-Duplex	metal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

