DATASHEET

Splice box gy sliding LC OM4 48x fanout pigtail and 24x duplex adapter (metal)











General data

completely assembled splice box with adapters and coloured pigtails
metal housing depth adjustable
cable entries at the rear, incl. 1 x PG16
6 x self adhesive fiber tray
Special assembly possible at short notice!

Technical properties

Adapter material	Metall adapter
Adapters	LC-Duplex
Depth	244.0 mm
Fibre class	OM4
Fibre type	Multi mode 50/125
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	stripped
Sliding	sliding
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Splice box gy sliding LC OM4 48x fanout pigtail and 24x duplex adapter (metal)

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
BA71902.12OM4	Splice box gy sliding LC OM4 12x fanout pigtail and 6x duplex adapter (metal)	grey	12 x LC	12	LC-Duplex	6	7035	LC-Duplex	metal
BA71902.24OM4	Splice box gy sliding LC OM4 24x fanout pigtail and 12x duplex adapter (metal)	grey	24 x LC	12	LC-Duplex	12	7035	LC-Duplex	metal
BA71902.48OM4	Splice box gy sliding LC OM4 48x fanout pigtail and 24x duplex adapter (metal)	grey	48 x LC	24	LC-Duplex	24	7035	LC-Duplex	metal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.