DATASHEET

SFP Fast Ethernet, SM, 100LX, 10km, 1310nm, 155Mbps, LC dplx, DDM











General data

The BlueOptics© BO05A13602 Small Form-Factor Pluggable (SFP) transceiver with LC duplex connector from CBO is designed for short-range multi-mode Fast Ethernet (FE), Fibre Channel over Ethernet (FCoE) applications of up to 155 megabits per second.

BlueOptics© SFP Transceiver
LC-Duplex
100BASE-LX
Singlemode Fiber
1310nm
10KM
0°C/+70°C
DDM

Technical properties

Compatible to	Standard
Connector	LC Duplex
Construction type	Mini GBIC
Fast Ethernet	True

This datasheet was created automatically on 23-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

SFP Fast Ethernet, SM, 100LX, 10km, 1310nm, 155Mbps, LC dplx, DDM

Fiber qualitiy	OS2
Mode	Singlemode
Protocol	100BaseLX
Range	10 km
Speed	100 Mbit/s
Temperature	0 – 70 °C
Wave length	1310 nm

Available variants

ArtNr.	Bezeichnung	Unique
BO05A13610D-BO	SFP Fast Ethernet, SM, 100LX, 10km, 1310nm, 155Mbps, LC dplx, DDM	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de