


DATASHEET

BlueOptics, Active Optical Cable, 2 x SFP+, 10GBASE-SR,
10m, MM G50/125µm



General data

For 10G Ethernet Data Center Intra-Rack and Inter-Rack links
Hot-pluggable SFP+ cable ends
Rigid pull-tab for improved high-density installations
Supports 10.3125 Gb/s bit rate
RoHS-6 compliant (lead-free)
SFI limiting interface
Single 3.3V power supply
Low power dissipation
Commercial temperature range: 0° C to 70° C

Technical properties

Compatible to | Standard

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

DATASHEET

BlueOptics, Active Optical Cable, 2 x SFP+, 10GBASE-SR, 10m, MM G50/125µm

Available variants

ArtNr.	Bezeichnung	Length
BO353503J10M-BO	BlueOptics, Active Optical Cable, 2 x SFP+, 10GBASE-SR, 10m, MM G50/125µm	10.0 m
BO353503J1M-BO	BlueOptics, Active Optical Cable, 2 x SFP+, 10GBASE-SR, 1m, MM G50/125µm	1.0 m
BO353503J3M-BO	BlueOptics, Active Optical Cable, 2 x SFP+, 10GBASE-SR, 3m, MM G50/125µm	3.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

