DATASHEET

Duplex Patchcable Push/Pull LC-LC OM3 7,5m LSZH 3mm aqua



General data

The LC HD Uniboot Jumper has a long unlock latch, due to unlock in the easiest way in HD patchpanel. The Polarity or Coding of the Duplex connector can be changed in the easiest way that it can reach the requirements of the application. The Jumper is available in the categories OM3, OM4 and G657A1.

Technical properties

Anti-kink sleeve	put-on
Bend optimized fiber	no
Cable structure	Duplex
Cable type	I-V(ZN) H
Cable Ø	3 mm
Category	OM3
Colour outer sheath	aqua
Fibre type	Multi mode 50/125
Flame retardant	acc. to IEC 60332-1-2
Halogen free	acc. to IEC 62821
Insertion loss 850nm	≤0,25 dB

This datasheet was created automatically on 16-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Duplex Patchcable Push/Pull LC-LC OM3 7,5m LSZH 3mm aqua

Low smoke	acc. to IEC 61034
Material outer sheath	LSZH
Min. Bending radius (Dynamic)	20xOD mm
Min. Bending radius (Static)	10xOD mm
Number of fibres	2
Operating Temperature	-20 – 60 °C
Packaging	EFB-Electronics poly bag (resealable)
Reinforcment	Aramid
Return loss 850nm	≥35 dB
Scope of delivery	1x Patchcable, 2x Duplex Clip, 1x Measurement Report, 1x Information Sheet
Storage Temperature	-20 – 70 °C
Type of connector connection 1	LC (Push/Pull)
Type of connector connection 2	LC (Push/Pull)

Available variants

ArtNr.	Bezeichnung	Length	Length tolerance
DJP-LCLCOM3-UNI-0,5	Duplex Patchcable Push/Pull LC-LC OM3 0,5m LSZH 3mm aqua	0.5 m	±5 %
DJP-LCLCOM3-UNI-1	Duplex Patchcable Push/Pull LC-LC OM3 1m LSZH 3mm aqua	1.0 m	±5 %
DJP-LCLCOM3-UNI-10	Duplex Patchcable Push/Pull LC-LC OM3 10m LSZH 3mm aqua	10.0 m	±5 %
DJP-LCLCOM3-UNI-15	Duplex Patchcable Push/Pull LC-LC OM3 15m LSZH 3mm aqua	15.0 m	±5 %
DJP-LCLCOM3-UNI-2	Duplex Patchcable Push/Pull LC-LC OM3 2m LSZH 3mm aqua	2.0 m	±5 %
DJP-LCLCOM3-UNI-20	Duplex Patchcable Push/Pull LC-LC OM3 20m LSZH 3mm aqua	20.0 m	±5 %
DJP-LCLCOM3-UNI-3	Duplex Patchcable Push/Pull LC-LC OM3 3m LSZH 3mm aqua	3.0 m	±5 %
DJP-LCLCOM3-UNI-5	Duplex Patchcable Push/Pull LC-LC OM3 5m LSZH 3mm aqua	5.0 m	±5 %
DJP-LCLCOM3-UNI-7,5	Duplex Patchcable Push/Pull LC-LC OM3 7,5m LSZH 3mm aqua	7.5 m	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 16-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION