

DATASHEET

Power Adapter IEC C14 - IEC C7, Cold Device Plug - Euro 8 Jack



General data

The IEC C14 to IEC C7 power adapter from EFB-Elektronik connects an IEC plug to a Euro 8 socket and is designed for compact power connections in technical applications. The black version with polyvinyl chloride (PVC) jacket supports a practical and robust connection solution.

- Designed for IEC C14 to IEC C7
- Connection 2 as C7 coupling 180°
- Two-pole design with 2 wires

The technical design focuses on a simple and standard-oriented connection between the IEC plug and the Euro 8 socket. The PVC sheath provides solid cable routing, while the black outer sheath colour allows for unobtrusive integration into existing installations.

Technical details

- Brand: EFB-Elektronik
- Connector 1: IEC plug
- Connector 2: C7 coupling 180°
- Core Count: 2
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)

Technical properties

Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	C7 plug female 180°
Halogen free	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Power Adapter IEC C14 - IEC C7, Cold Device Plug - Euro 8 Jack

Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	2
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	False
Spiralized cable	False
Type of packaging	Labeled polybag
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath
EB515.2	Power Adapter IEC C14 - IEC C7, Cold Device Plug - Euro 8 Jack	black

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

