DATASHEET

USB2.0/RS232 Converter Cable, FTDI-232RL chipset, USB A-Plug/DB9-Plug 1,8m



General data

USB A plug to DSub 9-pole plug, 1.8 metres
Supports RS-232, DB9, DB25
Connection of serial devices to USB
Power supply via USB interface
Chipset: FTDI-232RL
Supports WIN98SE/ME/2000/XP/VISTA/WIN7/8/10 LINUX/MACOS
Driver CD

Technical properties

Bi-directional	False
Connection type primary side	USB-A
Connection type secondary side	D-Sub plug 9-pole
Galvanic separation	None
Nominal electricity consumption	-
Over current protection	False
Service primary side	USB
Service secondary side	RS232
Transmission rate	1024 kBps

Available variants

ArtNr.	Bezeichnung	Unique
EB853C	USB2.0/RS232 Converter Cable, FTDI-232RL chipset, USB A-Plug/DB9-Plug 1,8m	Unique

This datasheet was created automatically on 03-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

USB2.0/RS232 Converter Cable, FTDI-232RL chipset, USB A-Plug/DB9-Plug 1,8m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 03-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION