

DATASHEET

Type-C adapter to DisplayPort 1.2 adapter, 4K60Hz, white



General data

This USB-C to DisplayPort adapter from EFB-Elektronik meets the requirements for DisplayPort 1.2 and enables a maximum resolution of up to 4K@60Hz. It supports the 4K UHD (Ultra High Definition) video standard and is particularly well-suited for TVs, monitors, and smartphones. The USB standard is backward compatible and suitable for many devices. Thanks to a bandwidth of 21.6 Gbit/s, even very high-quality media can be transmitted effortlessly.

- Adapter: Male to female connector for easy access to the right connections
- Connections: USB Type-C to DisplayPort connects compatible devices
- Cable type: Active signal attenuation and loss

Product Benefits: Media playback becomes even more vibrant thanks to HDR, which transmits a wider color spectrum and finer nuances of brightness.

Product Description: PVC cable jacket. The USB Type-C connector, USB Type-C socket, and DisplayPort socket have an ABS connector housing to prevent damage.

Technical Details

- Connector 1: USB Type-C male and female (24-pin)
- Connector 2: DisplayPort socket (20-pin)
- Connector angle: 180° (straight)
- Maximum transfer rate: 21.6 Gbps

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



DATASHEET

Type-C adapter to DisplayPort 1.2 adapter, 4K60Hz, white

- Supported technologies/protocols: HDR, Thunderbolt 3, DisplayPort Alternate Mode
- Contact material: Nickel-plated contact
- Signal type: Digital
- Cable diameter: 3.9 mm
- Jacket material: PVC
- Maximum mating cycles: 10,000
- With chip
- Brand: EFB-Elektronik

Scope of delivery

- 1 x USB-C to DisplayPort adapter

Technical properties	
3D	False
ARC	False
Backwards compatible	True
Bandwith	21.6 Gbit/s
Bending radius (dynamic/static)	39 mm
CEC	False
Cable set	False
Cable type (passive/active/optical)	active
Chip	True
Color depth	12-Bit
Compliant with	TV, Monitor, Smartphone, Tablet, Gaming monitor, Laptop
Compressions technologies	Dolby TrueHD
Connection type connection 1	Plug
Connection type connection 1b	Jack
Connection type connection 2	Jack
Connector 1 angulation	180°
Connector 2 angulation	180°
Contact Plating	nickel-plated
DSC	False
Dust cover	True
Enhanced Color	HighDynamicRange
HDMI Power	False
HDMI certified	False
HDR	HDR
HEC (Ethernet channel)	False
Halogenfree	No
Kink protection	True

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



DATASHEET

Type-C adapter to DisplayPort 1.2 adapter, 4K60Hz, white

MSA	False
MST	False
Material Connector Housing	ABS
Material Inner Conductor	TC
Material jacket	PVC
Max. mating cycles	10000
Max. resolution	4K@60Hz
Model	Round Cable
Number of poles connection 1	24
Number of poles connection 1b	24
Number of poles connection 2	20
Number of shieldings	triple
Operating temperature	0 – 45 °C
PCIe Data transfer	False
Plug dimensions Side 1	25mm x 12.2mm x 6.4mm
Plug dimensions Side 2	41.85mm x 37mm x 14.5mm
Scope of delivery	1x USB-C to DP adapter
Shielded	True
Speed	21.6 Gbit/s
Supported protocols / functions	DP Alternate Mode
Supported video standards	4K UHD - Ultra High Definition
Temperature	-10 – 5560 °C
Tensile strength (short/long)	29,4 N
Thunderbolt compatible	Thunderbolt 3
Type of connector connection 1	USB Type-C
Type of connector connection 1b	USB-C
Type of connector connection 2	DP
Type of packaging	recycled plastic bag
Type of signal	Digital
VESA certified	False
VRR	False
Version	DP1.2
Warranty	12 months
With termination resistor	True
eARC	False

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



DATASHEET

Type-C adapter to DisplayPort 1.2 adapter, 4K60Hz, white

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
EBUSBC-DP-4K60	Type-C adapter to DisplayPort 1.2 adapter, 4K60Hz, white	weiß	0.15 m	3.9 mm	34AWG
EBUSBC-DP-4K60-SW	Type-C adapter to DisplayPort 1.2 adapter, 4K60Hz, black	Black	0.15 m	3.9 mm	34AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.

