

DATASHEET

USB Type-C - DP1.2 Cable, USB Type-C male- DP20 male, 4K@60Hz, 2m



General data

Typ C to DisplayPort connection cable for connection between a USB Type-C device like PC/Notebook/Tablet to a HDMI display

Supports DP1.2 with max 4K/60Hz resolution

Support RGB/YCbCr 4:4:4/ YCbCr 4:2:2/ YCbCr 4:2:0

Supports Deep Color format: 6bit□8bit□10bit

HDR bypass

HDCP bypass

Thunderbolt 3 compatible

Technical properties

3D	False
ARC	False
Backwards compatible	True
Bandwith	21.6 Gbit/s

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

USB Type-C - DP1.2 Cable, USB Type-C male- DP20 male, 4K@60Hz, 2m

Bending radius (dynamic/static)	42 mm
CEC	False
Cable set	False
Cable type (passive/active/optical)	active
Chip	True
Color depth	12-Bit
Compliant with	TV, Monitor, Smartphone, Tablet, Gaming monitor, Laptop
Compressions technologies	Dolby TrueHD
Connection type connection 1	Plug
Connection type connection 2	Plug
Connector 1 angulation	180°
Connector 2 angulation	180°
Contact Plating	nickel-plated
DSC	False
Dust cover	True
Enhanced Color	HighDynamicRange
HDMI Power	False
HDMI certified	False
HDR	HDR
HEC (Ethernet channel)	False
Halogenfree	No
Kink protection	False
MSA	False
MST	False
Material Connector Housing	ABS
Material Inner Conductor	TC
Material jacket	TPE
Max. mating cycles	10000
Max. resolution	4K@60Hz
Model	Adapter
Number of poles connection 1	24
Number of poles connection 2	20
Number of shieldings	triple
Operating temperature	0 - 45 °C
PCIe Data transfer	False
Plug dimensions Side 1	22mm x 12.3mm x 6.3mm

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

USB Type-C - DP1.2 Cable, USB Type-C male- DP20 male, 4K@60Hz, 2m

Plug dimensions Side 2	41mm x 21mm x 12mm
Scope of delivery	1x USB-C to DP cable
Shielded	True
Speed	21.6 Gbit/s
Supported protocols / functions	DP Alternate Mode
Supported video standards	4K UHD - Ultra High Definition
Temperature	-10 - 5560 °C
Tensile strength (short/long)	29,4 N
Thunderbolt compatible	Thunderbolt 3
Type of connector connection 1	USB Type-C
Type of connector connection 2	DP
Type of packaging	recycled plastic bag
Type of signal	Digital
VESA certified	False
VRR	False
Version	DP1.2
Warranty	12 months
With termination resistor	True
eARC	False

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
EBUSBC-DP12K.2	USB Type-C - DP1.2 Cable, USB Type-C male- DP20 male, 4K@60Hz, 2m	Black	2.0 m	4.2 mm	34AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

