


DATASHEET

Power Cable UK BS1363A - C13 90°, Black, 1.8 m, 3 x 0.75 mm²



General data

The power cable UK BS1363A angled to IEC socket from EFB-Elektronik is designed as a black power cable UK BS1363A C13 with a length of 1.8 m for use in the UK. With a 90° angle at port 1 and an angled IEC socket at port 2, it is suitable for standard-compliant connection solutions in technical applications.

- Black version with 1.8 m cable length
- BS1363A plug with 90° angle and angled IEC socket with 180° design
- 3-core cable with protective conductor for use in the UK

The outer sheath made of polyvinyl chloride (PVC) supports robust and practical cable routing for device connections with defined plug-in geometries. The temperature range of 0 to 70 °C, the nominal voltage of 250 V and the nominal current of 10 A place the cable in a typical application framework for corresponding grid connections.

Technical details

- Brand: EFB-Elektronik
- Port 1: BS1363A
- Connector 1 angle: 90°
- Connection 2: Angled IEC socket
- Connector 2 angle: 180°

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C13 90°, Black, 1.8 m, 3 x 0.75 mm²

- Core Count: 3
- Outer jacket colour: black
- Operating temperature: 0 – 70 °C
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: UK

Technical properties

Bending radius (dynamic/static)	68 mm
Cable printing	H05VV-F 3G 0.75mm ² D S N FI ÖVE KEMA-KEUR IEMMEQU VDE N20050 GTSA-3 3G 0.75mm@ MSL CE
Colour outer sheath	black
Connection 1	BS1363A
Connection 2	Cold device plug angled, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	UK
Halogen free	False
Locking mechanism	False
Material outer sheath	PVC
Max. mating cycles	10000
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	0 – 70 °C
Protective conductor	True
Scope of delivery	Power cord
Security certificates	VDE
Spiralized cable	False
Storage Temperature	-10 – 80 °C
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C13 90°, Black, 1.8 m, 3 x 0.75 mm²

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK460.1,8	Power Cable UK BS1363A - C13 90°, Black, 1.8 m, 3 x 0.75 mm ²	black	1.8 m	10 A	250 V	Dca	0.75 mm ²	6.8 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.

