

DATASHEET

Power Cable South Afr. - C5 180°, Black, 1.8 m, 3 x 0.75 mm²



General data

The South Africa/India - C5 180° power cable, black from EFB-Elektronik is designed as a 3-wire cable with black outer jacket colour and a length of 1.8 m. With type M angled connection 1 and C5 cloverleaf coupling at port 2, it is suitable for compact mains connections in technical environments.

- Black version with a length of 1.8 m
- 3-wire power cable with protective conductor
- Port 1: Type M angled, Port 2: C5 cloverleaf coupling

The polyvinyl chloride (PVC) jacket supports a practical and resilient design for technical installations. The combination of angled Type M connector and C5 cloverleaf coupling ensures clear interface assignment to suitable devices and enables clean integration into existing connection concepts.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Type M angled
- Port 2: C5 cloverleaf coupling
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

Power Cable South Afr. - C5 180°, Black, 1.8 m, 3 x 0.75 mm²

- Protective conductor available

Technical properties

Colour outer sheath	black
Connection 1	Typ M angled
Connection 2	C5 Mickey Mouse female
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Type of packaging	Labeled polybag
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal cross section conductor	Outer diameter approx.
EK467.1,8	Power Cable South Afr. - C5 180°, Black, 1.8 m, 3 x 0.75 mm ²	black	1.8 m	0.75 mm ²	6.8 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

