

DATASHEET

Power Cable Japan Type B - C5 180°, Black, 1.8 m, VCTF 3 x 0.75 mm²



General data

The Japan Type B - C5 180° black power cable from EFB-Elektronik is designed for the connection between the Type B plug and the C5 cloverleaf coupling. With a length of 1.8 m, a black outer sheath and a protective conductor, it is suitable for compact power connections in technical applications.

- 3-wire version with protective conductor
- Port 1: Type B straight, Port 2: C5 cloverleaf coupling
- 1.8 m length with black outer jacket

The polyvinyl chloride (PVC) sheath supports robust and practical cable routing. The combination of a straight Type B connection and C5 cloverleaf coupling allows for clear integration into existing systems where a reliable power supply with a compact design is required.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Type B straight
- Port 2: C5 cloverleaf coupling
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.



DATASHEET

Power Cable Japan Type B - C5 180°, Black, 1.8 m, VCTF 3 x 0.75 mm²

- Protective conductor available

Technical properties

Colour outer sheath	black
Connection 1	Typ B straight
Connection 2	C5 Mickey Mouse female
Material outer sheath	PVC
Nominal voltage	125 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Type of packaging	Labeled polybag
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal cross section conductor	Outer diameter approx.
EK482.1,8	Power Cable Japan Type B - C5 180°, Black, 1.8 m, VCTF 3 x 0.75 mm ²	black	1.8 m	0.75 mm ²	6.8 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-09-2026 . Technical changes reserved.

