

DATASHEET

Power Cable Switzerland Type 12 - C13 90°, Black, 1.8 m, 3 x 0.75 mm²



General data

The Swiss Type 12 - C13 90° power cable in black version from EFB-Elektronik is designed for use in Switzerland and combines a Swiss standard type 12 with an angled IEC socket. With a length of 1.8 m, it is suitable for standard-compliant and practical connections in various applications.

- Suitable for Switzerland and designed for secure grid connection
- Connection 1 as Swiss standard type 12 with 180° angulation
- Connection 2 as an angled IEC socket with 90° angulation

The structure with three wires, protective conductor and sheath material made of polyvinyl chloride (PVC) supports a robust and technically functional design. With a nominal voltage of 250 V and a nominal current of 10 A, the Swiss Type 12 C13 1.8 m power cord is designed for common supply requirements.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connection 1: Swiss Standard Type 12
- Connector 1 angle: 180°
- Connection 2: Angled IEC socket
- Connector 2 angle: 90°

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

Power Cable Switzerland Type 12 - C13 90°, Black, 1.8 m, 3 x 0.75 mm²

- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available
- Country suitability: Switzerland

Technical properties

Cable printing	VDE H05VV-F 3G0.75mm² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Swiss norm type 12
Connection 2	Cold device plug angled, female
Connector 1 angulation	180 °
Connector 2 angulation	90 °
Country suitability	Suisse
Halogen free	No
Locking mechanism	False
Material outer sheath	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Operating temperature	
Plug imprint	R3-10 +S 250V 10A
Protective conductor	True
Security certificates	S
Spiralized cable	False
Storage Temperature	
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
--------	-------------	---------------------	----------------------	--------	-----------------	-----------------	---------------------------	---------------------------------	------------------------

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

Power Cable Switzerland Type 12 - C13 90°, Black, 1.8 m, 3 x 0.75 mm²

EK483.1,8V2	Power Cable Switzerland Type 12 - C13 90°, Black, 1.8 m, 3 x 0.75 mm ²	black	IP20	1.8 m	10 A	250 V	Ja	0.75 mm ²	6.5 mm
-------------	---	-------	------	-------	------	-------	----	----------------------	--------

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

